

Arm 2200 mm single attachment 120 mm

Design Massimiliano & Doriana Fuksas

iGuzzini

September 2012

Arm 2200 mm single attachment 120 mm -

Product code:

B442

Technical description:

Single extruded-aluminium arm subjected to phosphochromate treatment with double primer, passivation at 120° C, painting, baking at 150° C. The surface of the arm is painted with liquid paint. The power-supply cable (maximum section allowed 15 mm²) passes inside the arm. The attachment to the optical assembly in diecast aluminium is located at one end of the arm - fixed by two internal screws. The arm is coupled to the optical assembly by two safety bolts and two fixing screws in stainless steel. The flange is fixed to the pole by a counterflange, while the installation is ensured by stainless-steel nuts and screws M10. The flanges are made of chill-cast aluminium and subjected to phosphochromate treatment. Each flange is equipped with hexagonal elements that prevent the counterrotation of nuts and bolts in stainless steel. This prevents the product from rotating. A stainless-steel tie rod is located in the upper section with mechanical and aesthetical functions. It is fixed to the pole and arm by two chill-cast aluminium elements and is adjusted by means of the threads at its ends. All screws are made of stainless steel.

Installation:



Installation on pole 120 mm by flanges and fixing screws.

Dimension:

Double-T section 60x65 mm; L = 2200 mm

Colour:

Grey (15)



Complies with EN605981 and pertinent regulations

