

September 2012

Linealuce - x 1W warm white 3100K - wall washer optic**Product code:**

BA59

Technical description:

Luminaire with direct wall-washer emission designed for use with LED sources. Monochromatic, with plate for 28x1W Warm White (3100K) LEDs, optic with plastic lenses, SPOT version. Complete with lamp and built-in electronic ballast. Extruded aluminium body subjected to phosphochromatisation treatment, double primer, passivation at 120° C, die-cast aluminium end caps with 50/60 Shore A silicone gaskets subjected to post-cooling treatment at 200°C C. Acrylic liquid paint finish with high resistance to atmospheric agents and UV rays; baking at 150°C. The optical assembly is closed with sodium-calcium tempered transparent clear semi-acid finished glass with 4mm thickness fixed with silicone. Alluminium outer casing for installation with technopolymer caps to be ordered separately Ready for through wiring by means of two PG11 nickel-plated brass cable clamps suitable for \varnothing 6.5÷11mm cables contained in thermoplastic box fixed to the optical assembly. All external screws are made of stainless steel A2.

Installation:

Recessed installation in pavement, wall and ceiling with outer casing to be ordered separately.

Dimension:

117 x 101mm L=1268mm

Colour:

Grey (15)

Mounting:


Ceiling recessed|Ground recessed|Wall recessed

Wiring:

Electronic ballast inside the luminaire, 220÷240V 50÷60Hz.

Notes:

Available with Cool White (6700K), red, green and amber LED on demand. Available accessories: microperforated screen, chromatic filters, outer casing and safety cables for wall and ceiling installation.



Complies with EN605981 and pertinent regulations

