


September 2012

**Linealuce - DALI monochromatic LED warm white(27Wmax) - flood optic****Product code:**

BB88

Technical description:

Direct-light luminaire designed for use with DALI dimmable LED sources. Monochromatic, with plate for 27Wmax 15 Warm White (3100K) LEDs, optic with plastic lenses, FLOOD version. Complete with plastic translucid filter, lamp and Dali 48÷56Vdc control board. Electronic ballast to be ordered separately. Extruded aluminium body subjected to phosphochromatisation treatment, double primer, passivation at 120° C, die-cast aluminium end caps with 50/60 Shore A silicone gaskets subjected to post-cooling treatment at 200° C. Acrylic liquid paint finish with high resistance to atmospheric agents and UV rays; baking at 150°C.

The optical assembly is closed with sodium-calcium tempered transparent clear glass with 4 mm thickness fixed with silicone. PG11 nickel-plated brass cable clamps for \varnothing 6.5÷11mm cables, for single entrance for power supply cable. Antiglare screens and chromatic filters are available on demand. All external screws are made of stainless steel A2.

Installation:

Wall installation with brackets and extensible arms with $\pm 90^\circ$ orientation; ceiling installation with plate for surface-mounted application, suspension cables and rigid rods.

Dimension:

75 x 76mm L=942mm

Colour:

Grey (15)

Mounting:

Ceiling pendant|Ceiling surface|Wall surface

Wiring:

Complete with DALI 48-56Vdc control board. Electronic control gear to be ordered separately (code BZ14 - 100W Vin=100-240Vac Vout=48/56Vdc, code BZ15 - 240W Vin=100-240Vac Vout=48/56Vdc, code BZ16 - 480W Vin=100-240Vac Vout=48/56Vdc).

Notes:

Complete with lamp. The electronic board takes one Dali address, absorbs one Dali load and is equipped with DIRECT DIM, which provides the following functions by means of standard button: Soft ON/OFF, dimming, storage of last lux level.

Complies with EN605981 and pertinent regulations

