


Last information update: May 2018

**Recessed rectangular ceiling-mounted IP65 luminaire, compact body, Neutral White LEDs, Wide Flood optic.****Product code**

BX68

Technical description

Miniaturised recessed rectangular luminaire with ten optical elements with Neutral White LED light sources - fixed Wide Flood optic. Comprises a (round) optical compartment, frame, glass, outgoing cable and installation accessories to be ordered separately, where necessary. The optical compartment and frame are made of aluminium alloy and subjected to a multi-step pre-treatment process, the main phases of which include degreasing, fluorozirconic coating (a surface protective coat) and sealing (silane-based nanostructured coat). The successive painting phase is completed using primer and liquid acrylic paint, baked at 150°C, guaranteeing excellent resistance to atmospheric agents and UV rays. The glass-holder frame has plastic end caps. Tempered soda-lime closing glass, transparent with black screen-printing on the edge, 3mm thickness, attached to the frame with silicone. Silicone seals are placed between the glass-holder frame and the optical compartment. High-definition optic made of metallic thermoplastic, integrated into the black anti-glare screen towards the rear. Grade 304 stainless steel supporting springs. Equipped with IP65 control gear with outgoing cable for connection. The optical compartment and control gear are connected through IP68 quick-fit connectors. All external screws are made of A2 stainless steel.

Installation

Recessed installation with protruding frame on 1-20mm-thick suspended ceilings. Recess opening on suspended ceiling, size 274x37. Recessed installation with flush frame on 12.5mm- or 15mm-thick suspended ceilings, through adapter frame to be ordered separately. Installation on concrete ceilings using an outer casing to be ordered separately (flush and protruding frame).

Dimension (mm)

291x49x65

Colour

Black/White (47) | Grey/Black (74)

Weight (Kg)

1

Mounting

ceiling recessed

Wiring

Power supply unit inclusive of electronic control gear (220-240VAC 50/60Hz) with outgoing connection cable. IP68 connectors, to be ordered separately, are available for the electrical connections.

Notes

Version with black painted frame and DALI available on request.

Complies with EN60598-1 and pertinent regulations



IK06

IP65

**Product configuration: BX68****Product characteristics**

Total lighting output [Lm]: 1397
Total power [W]: 24.4
Luminous efficacy [Lm/W]: 57.3
Life Time: 50,000h - L90 - B10 (Ta 25°C)
Number of optical assemblies: 1


Total luminous flux at or above an angle of 90° [Lm]: 0
Emergency luminous flux [Lm]: /
Voltage [V]: -
Ambient temperature range: from -20°C to +35°C.

Optical assembly Characteristics Type 1


Light Output Ratio (L.O.R.) [%]: 76
Lamp code: LED
ZVEI Code: LED
Nominal power [W]: 21
Nominal luminous [Lm]: 1840
Lamp maximum intensity [cd]: /
Beam angle [°]: 48°

Number of lamps for optical assembly: 1
Socket: /
Ballast losses [W]: 3.4
Colour temperature [K]: 4000
CRI: 95
Wavelength [nm]: /
MacAdam Step: 3

Polar



Isolux



UGR diagram

Corrected UGR values (at 1840 lm bare lamp luminous flux)											
Reflect.: ceiling/cav walls work pl. Room dim x y		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
		viewed crosswise					viewed endwise				
2H	2H	1.1	1.6	1.4	1.8	2.1	1.1	1.6	1.4	1.8	2.1
	3H	1.1	1.5	1.4	1.8	2.0	1.0	1.5	1.3	1.7	2.0
	4H	1.0	1.4	1.3	1.7	2.0	1.0	1.4	1.3	1.7	2.0
	6H	1.0	1.4	1.3	1.7	2.0	0.9	1.3	1.2	1.6	1.9
	8H	1.0	1.3	1.3	1.7	2.0	0.9	1.2	1.2	1.5	1.9
	12H	1.0	1.3	1.3	1.6	2.0	0.8	1.2	1.2	1.5	1.9
4H	2H	1.0	1.4	1.3	1.7	2.0	1.0	1.4	1.3	1.7	2.0
	3H	0.9	1.2	1.3	1.6	1.9	0.9	1.3	1.3	1.6	1.9
	4H	0.8	1.2	1.2	1.5	1.9	0.8	1.2	1.2	1.5	1.9
	6H	0.8	1.1	1.2	1.5	1.9	0.8	1.1	1.2	1.4	1.9
	8H	0.8	1.1	1.2	1.5	1.9	0.7	1.0	1.2	1.4	1.8
	12H	0.8	1.0	1.3	1.5	1.9	0.7	0.9	1.1	1.4	1.8
8H	4H	0.7	1.0	1.2	1.4	1.8	0.8	1.1	1.2	1.5	1.9
	6H	0.7	0.9	1.2	1.4	1.9	0.8	1.0	1.2	1.4	1.9
	8H	0.7	0.9	1.2	1.4	1.9	0.7	0.9	1.2	1.4	1.9
	12H	0.8	0.9	1.3	1.4	1.9	0.7	0.9	1.2	1.4	1.9
12H	4H	0.7	0.9	1.1	1.4	1.8	0.8	1.0	1.3	1.5	1.9
	6H	0.7	0.9	1.2	1.3	1.8	0.8	1.0	1.3	1.4	1.9
	8H	0.7	0.9	1.2	1.4	1.9	0.8	0.9	1.3	1.4	1.9
Variations with the observer position at spacing:											
S =		6.2 / -0.5					6.2 / -0.5				
		9.0 / -0.9					9.0 / -0.9				
		11.0 / -7.2					11.0 / -7.2				