

Platea Pro

Design Jean Michel Wilmotte

iGuzzini

Last information update: June 2018



Platea Pro

Product code

ED65

Technical description

Flood optic outdoor luminaire, designed to use WNC (White 2700K, 4000K, 6000K) LED lamps and DMX512-RDM control. Made up of an optical assembly with a base and an aluminium alloy frame. The painting stage consists of a primer and a liquid acrylic paint, cured at 150 °C, with a high level of weather and UV ray resistance. With a 5 mm thick colourless transparent tempered sodium-calcium glass cover. The product can be tilted by +5°/-90° around the vertical plane with a 10° step graduated gauge and fitted with mechanical blocks that guarantee stable aiming of the beam of light. Horizontal aiming is performed using the slots in the base, which allow an ±30° adjustment. High visual comfort. Polymer optic lenses offering high yield and even light distribution. Complete with multi-LED power plate with individual white 2700K, 4000K and 6000K LEDs (WNC). Extractable control gear connected with quick-coupling connectors. 220-240V ac 50/60Hz electronic ballast. Replaceable control gear. All the screws used are made of A2 stainless steel.

Installation

The luminaire can be installed at ground level or on walls using the standard base. Spike accessory for ground installation.

Dimension (mm)

406x276

Colour

Grey (15)

Weight (Kg)

8.55


Mounting

wall arm|wall surface|ground anchored

Wiring

Luminaire ready for pass-through wiring. Product perfect watertightness at the power cable entry point is guaranteed by 2 nickel-plated brass M24x1.5 cable clamps, suitable for cables with a max external 14mm ø (1.5mm² cross section). Push in terminal board.

Complies with EN60598-1 and pertinent regulations



Product characteristics

Total lighting output [Lm]: 3080

Total power [W]: 34.5

Luminous efficacy [Lm/W]: 89.28

Ambient temperature range: from -20°C to +35°C. (*)

* Preliminary data

Total luminous flux at or above an angle of 90° [Lm]: 0

Emergency luminous flux [Lm]: /

Voltage [V]: -

Number of optical assemblies: 1

Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: /

Lamp code: /

ZVEI Code: LED

Nominal power [W]: 28

Nominal luminous [Lm]: 3950

Lamp maximum intensity [cd]: /

Beam angle [°]: 44

Number of lamps for optical assembly: 1

Socket: /

Ballast losses [W]: /

Colour temperature [K]: 0

CRI: 80

Wavelength [Nm]: /

MacAdam Step: /