


Last information update: June 2018

**Pole-mounted system - ST1 optic - Neutral White - MidNight - ø42-60-76mm****Product code**

EH59

Technical description

Outdoor luminaire with direct light street optic, designed to use LED lamps. The optical assembly and the pole attachment system are made of EN1706AC 46100LF aluminium alloy, subjected to a multi-step, pre-treatment process, in which the main phases are degreasing, fluorozirconation (a protective surface film) and sealing (with a nano-structured silane layer). The painting stage consists of a primer and a textured liquid acrylic paint, cured at 150 °C, with a high level of weather and UV ray resistance. Option of adjusting the inclination in relation to the road surface of +20°/-5° (in 5° steps) for a pole-top installation and +5°/20° (in 5° steps) for a lateral installation. 5 mm thick sodium-calcium closing glass secured to product with 4 screws. The high IP rating is guaranteed by the silicone gasket placed between the two elements. Complete with monochrome LED circuit and polymer optic multilayer lenses. Electronic control gear with 100%-70% Middle of the Night profile. Driver with automatic internal temperature control system. Overvoltage protection: 10KV Common Mode and 6KV Differential Mode. Optic and wiring compartment can be opened with everyday tools. The light flow emitted in the upper hemisphere of the system in the horizontal position is null (in conformity with the strictest standards for the prevention of light pollution). All external screws are made of stainless steel.

Installation

The floodlight can be installed with pole-top or lateral mounting using a die-cast aluminium pole-top for end diameters of ø 42/60/76 mm.

Dimension (mm)

529x268x204

Colour

Grey (15)


Weight (Kg)

6.05

Mounting

wall arm|pole-top

Complies with EN60598-1 and pertinent regulations

**Product configuration: EH59****Product characteristics**

Total lighting output [Lm]: 4460
 Total power [W]: 33.9
 Luminous efficacy [Lm/W]: 131.6
 Life Time: 100,000h - L90 - B10 (Ta 25°C)
 Life Time: 100,000h - L90 - B10 (Ta 40°C)
 Ambient temperature range: from -20°C to +35°C. (*)

* Preliminary data

Total luminous flux at or above an angle of 90° [Lm]: 0
 Emergency luminous flux [Lm]: /
 Voltage [V]: 230
 Life Time: 100,000h - L80 - B10 (Ta 25°C)
 Life Time: 100,000h - L80 - B10 (Ta 40°C)
 Number of optical assemblies: 1

Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 100
 Lamp code: LED
 ZVEI Code: LED
 Nominal power [W]: /
 Nominal luminous [Lm]: /
 Lamp maximum intensity [cd]: /
 Beam angle [°]: /

Number of lamps for optical assembly: 1
 Socket: /
 Ballast losses [W]: 3.9
 Colour temperature [K]: 4000
 CRI: 70
 Wavelength [nm]: /
 MacAdam Step: 5

A candela diagram (photometric curve) showing the beam spread and throw of a lighting fixture. The diagram is a polar plot with concentric circles representing beam diameter (6000, 12000, 18000, 24000, 30000, 36000) and radial lines representing beam angle (0°, 90°, 180°). The fixture is labeled with the following specifications:

- Imax=3727 cd** (Maximum Candela)
- C15-195 $\gamma=70^\circ$** (Beam diameter and throw)
- CIE** (Color Rendering Index)
- LA^{0.5}=305** (Beam diameter at 0.5% illuminance)
- SPREAD=narrow** (Beam spread)
- THROW=intermediate** (Beam throw)
- SLI=6.9** (Spotlight Illuminance Index)
- DIN** (DIN standard)
- KB1** (KB1 standard)
- CEN** (CEN standard)
- G*3** (G*3 standard)
- D6** (D6 standard)

L/H	RS (eta)	KS (eta)
0	0.00	0.00
1	0.55	0.18
2	0.72	0.21
3	0.76	0.22
4	0.77	0.22