

Last information update: June 2018

**extractable, adjustable, recessed LED luminaire - electronic control gear included****Product code**

MU42

**Technical description**

Extractable, adjustable, recessed luminaire for warm white LED lamp with high color rendering index. Passive heat dispersion system. Die-cast aluminium main body and frame; stainless steel rotation hinge. Rotation ring with safety cover in a high resistance thermoplastic material. Body adjusted with a manual manoeuvre device: internal 40° - external 65° - rotation on 355° axis. Reflector with high efficiency super-pure aluminium optic - spot beam angle. Die-cast aluminium lamp body closure ring. Tempered transparent glass screen. Electronic control gear supplied and connected to the luminaire.

**Installation**

recessed using steel springs in false ceilings with thicknesses starting at 1 mm; preparation hole Ø 125 mm

**Dimension (mm)**

Ø136x98

**Colour**

White (01)

**Weight (Kg)**

0,85

**Mounting**

ceiling recessed

**Wiring**

on control gear box with quick-coupling connections

Complies with EN60598-1 and pertinent regulations

IP20

IP23

On the visible part of the product once installed

**Product configuration: MU42****Product characteristics**


Total lighting output [Lm]: 1540  
 Total power [W]: 18.8  
 Luminous efficacy [Lm/W]: 81.9  
 Life Time: 50,000h - L80 - B10 (Ta 25°C)

Total luminous flux at or above an angle of 90° [Lm]: 0  
 Emergency luminous flux [Lm]: /  
 Voltage [V]: -  
 Number of optical assemblies: 1


**Optical assembly Characteristics Type 1**

Light Output Ratio (L.O.R.) [%]: 77  
 Lamp code: LED  
 ZVEI Code: LED  
 Nominal power [W]: 15  
 Nominal luminous [Lm]: 2000  
 Lamp maximum intensity [cd]: /  
 Beam angle [°]: 18°

Number of lamps for optical assembly: 1  
 Socket: /  
 Ballast losses [W]: 3.8  
 Colour temperature [K]: 3000  
 CRI: 90  
 Wavelength [Nm]: /  
 MacAdam Step: 2



**Polar**



**Utilisation factors**

R	77	75	73	71	55	53	33	00	DRR
K0.8	68	63	61	58	63	60	60	57	74
1.0	71	67	65	63	66	64	64	61	79
1.5	75	72	70	68	71	69	69	66	86
2.0	78	76	74	73	75	73	72	70	91
2.5	79	78	76	75	77	75	75	72	94
3.0	80	79	78	77	78	77	76	74	96
4.0	81	80	80	79	79	79	77	75	98
5.0	82	81	81	80	80	79	78	76	99

**Luminance curve limit**

