

Laser Pinhole

Design iGuzzini

iGuzzini

Last information update: May 2018



recessed adjustable

Product code
P428

Technical description

Square adjustable luminaire designed for housing 3000K Warm White COB LED light sources with high colour rendering and OPTIBEAM reflector made of thermoplastic material. Rim made of white-coated die-cast aluminium incorporating a black-coated thermoplastic component for guaranteeing maximum visual comfort and preventing stray light dispersion. Flood optic. Adjustable internally around the horizontal axis by 35° and around the vertical axis by 358°. Passive cooling system, by means of a black-coated heat sink made of extruded aluminium. The power supply unit is available with a separate code.

Installation

Recessed installation in false ceilings with 1 mm to 20 mm thickness with steel springs.

Dimension (mm)
85x85x100

Colour
White (01)

Mounting
ceiling surface

Wiring

Constant-current ballasts available with separate code: ON-OFF / 1-10 V dimmable / phase-cut dimmer / the recessed luminaire is supplied with the cable and connector to be connected to the connector provided on the driver.

Complies with EN60598-1 and pertinent regulations



Product configuration: P428

Product characteristics

Total lighting output [Lm]: 490
Total power [W]: 10
Luminous efficacy [Lm/W]: 49
Life Time: > 50,000h - L80 - B10 (Ta 25°C)


Total luminous flux at or above an angle of 90° [Lm]: 0
Emergency luminous flux [Lm]: /
Voltage [V]: -
Number of optical assemblies: 1

Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 41
Lamp code: LED
ZVEI Code: LED
Nominal power [W]: 10
Nominal luminous [Lm]: 1200
Lamp maximum intensity [cd]: /
Beam angle [°]: 26°

Number of lamps for optical assembly: 1
Socket: /
Ballast losses [W]: 0
Colour temperature [K]: 3000
CRI: 90
Wavelength [Nm]: /
MacAdam Step: 2


Polar



Utilisation factors

R	77	75	73	71	55	53	33	00	DRR
K0.8	37	35	33	32	34	33	33	32	78
1.0	38	37	35	34	36	35	35	34	82
1.5	40	39	38	37	39	38	37	36	88
2.0	42	41	40	39	40	39	39	38	93
2.5	42	42	41	41	41	41	40	39	95
3.0	43	42	42	42	42	41	41	40	97
4.0	43	43	43	42	42	42	41	41	99
5.0	44	43	43	43	43	43	42	41	100

Luminance curve limit



UGR diagram

Corrected UGR values (at 1200 lm bare lamp luminous flux)											
Reflect.:		viewed crosswise					viewed endwise				
ceill/cav		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim		viewed crosswise					viewed endwise				
x	y										
2H	2H	2.4	4.6	2.8	4.9	5.2	2.4	4.6	2.8	4.9	5.2
	3H	2.7	4.3	3.1	4.7	5.0	2.6	4.3	3.0	4.6	4.9
	4H	2.8	4.1	3.1	4.4	4.8	2.6	4.0	3.0	4.3	4.6
	6H	2.8	3.8	3.2	4.1	4.4	2.6	3.6	3.0	3.9	4.3
	8H	2.8	3.7	3.2	4.1	4.4	2.6	3.6	3.0	3.9	4.3
	12H	2.8	3.7	3.2	4.1	4.5	2.6	3.5	3.0	3.8	4.2
4H	2H	2.6	4.0	3.0	4.3	4.6	2.8	4.1	3.1	4.4	4.8
	3H	3.0	3.9	3.4	4.3	4.7	3.0	4.0	3.4	4.3	4.7
	4H	3.0	3.9	3.5	4.3	4.7	3.0	3.9	3.5	4.3	4.7
	6H	2.8	4.5	3.2	4.9	5.4	2.7	4.4	3.2	4.8	5.3
	8H	2.7	4.6	3.2	5.1	5.6	2.6	4.5	3.1	5.0	5.5
	12H	2.7	4.6	3.2	5.1	5.6	2.5	4.5	3.0	5.0	5.5
8H	4H	2.6	4.5	3.1	5.0	5.5	2.7	4.6	3.2	5.1	5.6
	6H	2.6	4.4	3.1	4.9	5.5	2.7	4.5	3.2	5.0	5.5
	8H	2.7	4.3	3.2	4.8	5.4	2.7	4.3	3.2	4.8	5.4
	12H	2.9	4.1	3.5	4.6	5.1	2.9	4.0	3.4	4.5	5.0
12H	4H	2.5	4.5	3.0	5.0	5.5	2.7	4.6	3.2	5.1	5.6
	6H	2.6	4.2	3.2	4.7	5.3	2.8	4.4	3.3	4.9	5.4
	8H	2.9	4.0	3.4	4.5	5.0	2.9	4.1	3.5	4.6	5.1
Variations with the observer position at spacing:											
S =	1.0H	0.8 / -0.8					0.8 / -0.8				
	1.5H	1.8 / -2.1					1.8 / -2.1				
	2.0H	3.1 / -3.4					3.1 / -3.4				