

Last information update: June 2018



spotlight - warm white medium optic

Product code
P661

Technical description

Adjustable spotlight with adapter for installation on DALI track. Warm White (3000K) LED source with COB technology. DALI dimmable control gear housed inside the track-mounted power supply box. The luminaire is made of die-cast aluminium and thermoplastic. OPTI BEAM superpure aluminium reflector with high luminous efficacy and uniform distribution, medium optic. Features 90° inclination on the horizontal plane and 360° rotation around the vertical axis, with mechanical locking device for aiming. Passive cooling system. Possibility of installing a refractor, to be ordered separately, for elliptical light beam distribution.

Installation

The luminaire can be installed on a standard track, false ceilings or on an appropriate channel incorporating an electrified track.

Dimension (mm)
Ø65x140

Colour
White (01) | Black (04)

Weight (Kg)
0.68

Mounting

three circuit track|ceiling surface

Wiring

product inclusive of DALI dimmable components incorporated into the track-mounted box.

Complies with EN60598-1 and pertinent regulations

IP20 IP40 for optical assembly



Product configuration: P661

Product characteristics

Total lighting output [Lm]: 1184
Total power [W]: 15.4
Luminous efficacy [Lm/W]: 76.9
Life Time: > 50,000h - L80 - B10 (Ta 25°C)

Total luminous flux at or above an angle of 90° [Lm]: 0
Emergency luminous flux [Lm]: /
Voltage [V]: -
Number of optical assemblies: 1

Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 74
Lamp code: LED
ZVEI Code: LED
Nominal power [W]: 14
Nominal luminous [Lm]: 1600
Lamp maximum intensity [cd]: /
Beam angle [°]: 26°

Number of lamps for optical assembly: 1
Socket: /
Ballast losses [W]: 1.4
Colour temperature [K]: 3000
CRI: 90
Wavelength [Nm]: /
MacAdam Step: 2

Polar

