

Last information update: June 2018



**spotlight - DALI dimmable warm white spot optic**

**Product code**

P670

**Technical description**

Adjustable spotlight with adapter for installation on DALI track for LED source with COB technology, Warm White (3000K) emission. DALI control gear housed inside the track-mounted power supply box. The luminaire is made of die-cast aluminium and thermoplastic. OPTI BEAM superpure aluminium reflector with high luminous efficacy and uniform distribution, spot optic. Features 90° inclination on the horizontal plane and 360° rotation around the vertical axis, with mechanical locking device for aiming. Passive cooling system. Possibility of installing a refractor, to be ordered separately, for elliptical light beam distribution.

**Installation**

The luminaire can be installed on a DALI track or on an appropriate channel incorporating an electrified track.

**Dimension (mm)**

Ø86x189

**Colour**

White (01) | Black (04)

**Weight (Kg)**

1.12

**Mounting**

three circuit track|ceiling surface

**Wiring**

product inclusive of DALI components incorporated into the track-mounted box.

Complies with EN60598-1 and pertinent regulations

IP20 IP40 for optical assembly



**Product configuration: P670**

**Product characteristics**


Total lighting output [Lm]: 2040  
 Total power [W]: 23.4  
 Luminous efficacy [Lm/W]: 87.2  
 Life Time: > 50,000h - L80 - B10 (Ta 25°C)

Total luminous flux at or above an angle of 90° [Lm]: 0  
 Emergency luminous flux [Lm]: /  
 Voltage [V]: -  
 Number of optical assemblies: 1

**Optical assembly Characteristics Type 1**

Light Output Ratio (L.O.R.) [%]: 68  
 Lamp code: LED  
 ZVEI Code: LED  
 Nominal power [W]: 21  
 Nominal luminous [Lm]: 3000  
 Lamp maximum intensity [cd]: /  
 Beam angle [°]: 18°

Number of lamps for optical assembly: 1  
 Socket: /  
 Ballast losses [W]: 2.4  
 Colour temperature [K]: 3000  
 CRI: 80  
 Wavelength [Nm]: /  
 MacAdam Step: 2



**Polar**

