



Deep Minimal

Design iGuzzini

iGuzzini

Last information update: May 2018



Deep Minimal - 2 elements - CoB warm LED - flood beam - dimmable DALI

Product code

P912

Technical description

Two element recessed luminaire for LED lamps. Minimal (frameless) version with no contact frame. Shaped stainless steel sheet structural frame specifically designed for flush with ceiling application using the adapter supplied. Die-cast aluminium, twin swivel universal joints located in a position set back from the installation surface to guarantee a high level of visual comfort. Tilts $\pm 30^\circ$ around both the horizontal and vertical axes. Die-cast aluminium lighting bodies designed to optimise heat dispersal. High efficiency aluminium reflectors - flood angle. High color rendering index, warm white LED lamps. Each lamp unit has its own glass cover. Control gear unit included.

Installation

Recessed in 12.5 mm thick false ceilings. The aluminium adapter is designed for filling, smoothing and finishing the false ceiling before inserting the recessed unit. Steel wire fixing springs. Preparation hole 106 x 191

Dimension (mm)

185x100x89

Colour

White (01) | Black (04)

Weight (Kg)

1.2

Mounting

ceiling recessed

Wiring

Complete with DALI dimmable control gear unit connected to the luminaire. Wiring for connecting to mains network on driver terminal board.

Notes

Accessories available: refractor for elliptical flow distribution - interchangeable reflectors - adapter for installation in 15 mm thick false ceilings

Complies with EN60598-1 and pertinent regulations

IP20 IP23 On the visible part of the product once installed



Product configuration: P912

Product characteristics

Total lighting output [Lm]: 1498.7
Total power [W]: 21.5
Luminous efficacy [Lm/W]: 69.7
Life Time: > 50,000h - L80 - B10 (Ta 25°C)

Total luminous flux at or above an angle of 90° [Lm]: 0
Emergency luminous flux [Lm]: /
Voltage [V]: -
Number of optical assemblies: 2

Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 79
Lamp code: LED
ZVEI Code: LED
Nominal power [W]: 8.4
Nominal luminous [Lm]: 950
Lamp maximum intensity [cd]: /
Beam angle [$^\circ$]: 42°

Number of lamps for optical assembly: 1
Socket: /
Ballast losses [W]: 2.4
Colour temperature [K]: 3000
CRI: 90
Wavelength [nm]: /
MacAdam Step: 3

	CIE nL 0.79 99-100-100-100-79 UGR <10<10 DIN A.61 UTE 0.79A+0.00T F*1=991 F*1+F*2=999 F*1+F*2+F*3=1000 CIBSE LG3 L<500 cd/m² at 65° BZ1		Lux			
	h	d	Em	E_{max}		
	2	1.5	328	410		
	4	3.1	82	102		
	6	4.6	36	46		
8	6.1	21	26			

R	77	75	73	71	55	53	33	00	DRR
K0.8	71	67	65	63	67	64	64	61	78
1.0	74	71	68	67	70	68	68	65	82
1.5	78	75	73	72	74	73	72	70	88
2.0	80	78	77	76	77	76	75	73	93
2.5	82	80	79	78	79	78	77	75	95
3.0	83	82	81	80	81	80	79	77	98
4.0	84	83	83	82	82	81	80	78	99
5.0	84	84	83	83	82	82	81	79	100

QC	A	G	1.15	2000	1000	500	<=300	<=300	<=300
	B		1.50		2000	1000	750	500	<=300
	C		1.85			2000		1000	500

85°
75°
65°
55°
45°

10² 2 3 4 5 6 8 10³ 2 3 4 5 6 8 10⁴ cd/m²

C0-180 C90-270

UGR diagram

Photometric curve code: P8900000.RV0 Corrected UGR values (at 950 lm bare lamp luminous flux)											
Reflect.: ceiling/cav walls work pl. Room dim x y		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
		viewed crosswise					viewed endwise				
2H	2H	3.6	4.2	3.9	4.4	4.7	3.6	4.2	3.9	4.4	4.7
	3H	3.5	4.0	3.8	4.3	4.6	3.6	4.1	3.9	4.4	4.6
	4H	3.5	3.9	3.8	4.2	4.5	3.5	4.0	3.8	4.3	4.6
	6H	3.4	3.8	3.7	4.1	4.5	3.4	3.9	3.8	4.2	4.5
	8H	3.4	3.8	3.7	4.1	4.4	3.4	3.8	3.8	4.2	4.5
	12H	3.3	3.7	3.7	4.1	4.4	3.4	3.8	3.7	4.1	4.5
4H	2H	3.5	4.0	3.8	4.3	4.6	3.5	3.9	3.8	4.2	4.5
	3H	3.4	3.8	3.8	4.1	4.5	3.4	3.8	3.8	4.1	4.5
	4H	3.3	3.7	3.7	4.0	4.4	3.3	3.7	3.7	4.0	4.4
	6H	3.2	3.5	3.7	3.9	4.4	3.2	3.5	3.7	3.9	4.4
	8H	3.2	3.5	3.6	3.9	4.3	3.2	3.5	3.6	3.9	4.3
	12H	3.2	3.4	3.6	3.8	4.3	3.1	3.4	3.6	3.8	4.3
8H	4H	3.2	3.5	3.6	3.9	4.3	3.2	3.5	3.6	3.9	4.3
	6H	3.1	3.3	3.6	3.8	4.3	3.1	3.3	3.6	3.8	4.3
	8H	3.1	3.3	3.5	3.7	4.2	3.1	3.3	3.5	3.7	4.2
	12H	3.0	3.2	3.5	3.7	4.2	3.0	3.2	3.5	3.7	4.2
12H	4H	3.1	3.4	3.6	3.8	4.3	3.2	3.4	3.6	3.8	4.3
	6H	3.0	3.3	3.5	3.7	4.2	3.1	3.3	3.6	3.7	4.2
	8H	3.0	3.2	3.5	3.7	4.2	3.0	3.2	3.5	3.7	4.2
Variations with the observer position at spacing: S = 1.0H 5.3 / -4.9 5.3 / -4.9 1.5H 8.0 / -7.8 8.0 / -7.8 2.0H 9.9 / -11.8 9.9 / -11.8											