

## Deep Frame

Design iGuzzini

iGuzzini

Last information update: April 2018



### Deep Frame - 1 element - CoB warm LED - flood beam

#### Product code

P917

#### Technical description

Individual recessed luminaire for LED lamp. Version with a perimeter frame. Shaped sheet steel structural frame. Die-cast aluminium, twin swivel universal joint located in a position set back from the installation surface to guarantee a high level of visual comfort. Tilts  $\pm 30^\circ$  around both the horizontal and vertical axes. Die-cast aluminium lighting body designed to optimise heat dispersal. High efficiency aluminium reflector - flood angle. High color rendering index, warm white LED lamp. Glass cover Mechanical installation system. Control gear unit included.

#### Installation

Recessed in 1 to 30mm thick false ceilings - secured with manually adjustable metal brackets. Preparation hole 167 x 167.

#### Dimension (mm)

180x180x127

#### Colour

White (01) | Grey/Black (74)

#### Weight (Kg)

1.5

#### Mounting

ceiling recessed

#### Wiring

Complete with electronic control gear unit connected to the luminaire. Wiring for connecting to mains network on driver terminal board

#### Notes

Accessories available: refractor for elliptical flow distribution.

Complies with EN60598-1 and pertinent regulations

IP20 IP23 On the visible part of the product once installed



#### Product configuration: P917

#### Product characteristics


Total lighting output [Lm]: 2477  
Total power [W]: 30.8  
Luminous efficacy [Lm/W]: 80.4  
Life Time: > 50,000h - L80 - B10 (Ta 25°C)

Total luminous flux at or above an angle of  $90^\circ$  [Lm]: 0  
Emergency luminous flux [Lm]: /  
Voltage [V]: -  
Number of optical assemblies: 1


#### Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 80  
Lamp code: LED  
ZVEI Code: LED  
Nominal power [W]: 27  
Nominal luminous [Lm]: 3100  
Lamp maximum intensity [cd]: /  
Beam angle [ $^\circ$ ]:  $38^\circ$

Number of lamps for optical assembly: 1  
Socket: /  
Ballast losses [W]: 3.8  
Colour temperature [K]: 3000  
CRI: 90  
Wavelength [Nm]: /  
MacAdam Step: 3




**Polar**



**Utilisation factors**

R	77	75	73	71	55	53	33	00	DRR
K0.8	72	68	65	63	67	65	64	62	78
1.0	75	72	69	67	71	69	68	66	82
1.5	79	76	74	73	75	73	73	70	88
2.0	81	79	78	77	78	77	76	74	92
2.5	83	81	80	79	80	79	78	76	95
3.0	84	83	82	81	82	81	80	78	97
4.0	85	84	84	83	83	82	81	79	99
5.0	85	85	84	84	83	83	82	80	100

**Luminance curve limit**



**UGR diagram**

Corrected UGR values (at 3100 lm bare lamp luminous flux)											
Reflect.:											
ceiling/cav		0.70	0.70	0.50	0.50	0.30	0.70	0.70	0.50	0.50	0.30
walls		0.50	0.30	0.50	0.30	0.30	0.50	0.30	0.50	0.30	0.30
work pl.		0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20	0.20
Room dim		viewed					viewed				
x	y	crosswise					endwise				
2H	2H	12.8	13.4	13.1	13.7	13.9	12.8	13.4	13.1	13.7	13.9
	3H	12.7	13.2	13.0	13.5	13.8	12.7	13.2	13.0	13.5	13.8
	4H	12.6	13.1	12.9	13.4	13.7	12.6	13.1	12.9	13.4	13.7
	6H	12.5	13.0	12.9	13.3	13.6	12.5	13.0	12.9	13.3	13.6
	8H	12.5	13.0	12.9	13.3	13.6	12.5	13.0	12.9	13.3	13.6
	12H	12.5	12.9	12.8	13.2	13.6	12.5	12.9	12.8	13.2	13.6
4H	2H	12.6	13.1	12.9	13.4	13.7	12.6	13.1	12.9	13.4	13.7
	3H	12.5	12.9	12.8	13.2	13.6	12.5	12.9	12.8	13.2	13.6
	4H	12.4	12.8	12.8	13.1	13.5	12.4	12.8	12.8	13.1	13.5
	6H	12.3	12.6	12.7	13.0	13.4	12.3	12.6	12.7	13.0	13.4
	8H	12.2	12.6	12.7	13.0	13.4	12.2	12.6	12.7	13.0	13.4
	12H	12.2	12.5	12.7	12.9	13.4	12.2	12.5	12.7	12.9	13.4
8H	4H	12.2	12.6	12.7	13.0	13.4	12.2	12.6	12.7	13.0	13.4
	6H	12.2	12.4	12.6	12.9	13.3	12.2	12.4	12.6	12.9	13.3
	8H	12.1	12.3	12.6	12.8	13.3	12.1	12.3	12.6	12.8	13.3
	12H	12.1	12.2	12.6	12.7	13.2	12.1	12.2	12.6	12.7	13.2
12H	4H	12.2	12.5	12.7	12.9	13.4	12.2	12.5	12.7	12.9	13.4
	6H	12.1	12.3	12.6	12.8	13.3	12.1	12.3	12.6	12.8	13.3
	8H	12.1	12.2	12.6	12.7	13.2	12.1	12.2	12.6	12.7	13.2
Variations with the observer position at spacing:											
S =	1.0H	5.7 / -12.8					5.7 / -12.8				
	1.5H	8.5 / -14.7					8.5 / -14.7				
	2.0H	10.5 / -17.4					10.5 / -17.4				