


Laser Blade XS

Design iGuzzini

iGuzzini

Last information update: June 2018



Frame 5 cells - Medium beam - LED

Product code

Q495

Technical description

Linear miniaturised recessed luminaire with 5 optical elements for LED lamps - fixed optics. Despite the ultracompact size of the product, the patented technology of the optic system guarantees an efficient flow and a high level of controlled glare visual comfort. Main body with die-cast aluminium radiant surface, version with perimeter surface frame. Metallised, thermoplastic, high definition Opti Beam reflectors, integrated in a set-back position in the anti-glare screen. Supplied with DALI power supply unit connected to the luminaire.

Installation

Recessed with steel wire springs for false ceilings from 1 to 25 mm thick - preparation hole 24 x 96.

Dimension (mm)

100x28x50

Colour

White (01) | White/Brass (41) | Black/Black (43) | Black/White (47) | Grey/Black (74) | (E7)

Weight (Kg)

0.35

Mounting

wall recessed|ceiling recessed

Wiring

On the power supply unit with terminal board included.

Notes

.

Complies with EN60598-1 and pertinent regulations



Product configuration: Q495

Product characteristics


Total lighting output [Lm]: 624
Total power [W]: 12.4
Luminous efficacy [Lm/W]: 50.3
Life Time: > 50,000h - L80 - B10 (Ta 25°C)

Total luminous flux at or above an angle of 90° [Lm]: 0
Emergency luminous flux [Lm]: /
Voltage [V]: 230
Number of optical assemblies: 1

Optical assembly Characteristics Type 1

Light Output Ratio (L.O.R.) [%]: 79
Lamp code: LED
ZVEI Code: LED
Nominal power [W]: 9.8
Nominal luminous [Lm]: 790
Lamp maximum intensity [cd]: /
Beam angle [°]: 24°

Number of lamps for optical assembly: 1
Socket: /
Ballast losses [W]: 2.6
Colour temperature [K]: 3000
CRI: 90
Wavelength [Nm]: /
MacAdam Step: 3



UGR diagram

| Corrected UGR values (at 790 lm bare lamp luminous flux) | | | | | | | | | | | | |
|--|-----|---------------------|--------------|------|------|------|-------------------|--------------|------|------|------|------|
| Reflect.: ceiling/cav walls work pl. Room dim x y | | 0.70 | 0.70 | 0.50 | 0.50 | 0.30 | 0.70 | 0.70 | 0.50 | 0.50 | 0.30 | 0.30 |
| | | 0.50 | 0.30 | 0.50 | 0.30 | 0.30 | 0.50 | 0.30 | 0.50 | 0.30 | 0.30 | 0.30 |
| | | 0.20 | 0.20 | 0.20 | 0.20 | 0.20 | 0.20 | 0.20 | 0.20 | 0.20 | 0.20 | 0.20 |
| | | viewed crosswise | | | | | viewed endwise | | | | | |
| 2H | 2H | 2.5 | 4.7 | 2.9 | 5.0 | 5.3 | 2.5 | 4.7 | 2.9 | 5.0 | 5.3 | |
| | 3H | 2.4 | 4.0 | 2.8 | 4.3 | 4.7 | 2.4 | 4.0 | 2.8 | 4.3 | 4.7 | |
| | 4H | 2.3 | 3.7 | 2.7 | 4.0 | 4.4 | 2.3 | 3.7 | 2.7 | 4.0 | 4.3 | |
| | 6H | 2.3 | 3.3 | 2.7 | 3.7 | 4.0 | 2.3 | 3.3 | 2.7 | 3.7 | 4.0 | |
| | 8H | 2.3 | 3.3 | 2.7 | 3.6 | 4.0 | 2.2 | 3.3 | 2.6 | 3.6 | 4.0 | |
| | 12H | 2.2 | 3.2 | 2.6 | 3.6 | 4.0 | 2.2 | 3.2 | 2.6 | 3.6 | 4.0 | |
| 4H | 2H | 2.3 | 3.7 | 2.7 | 4.0 | 4.3 | 2.3 | 3.7 | 2.7 | 4.0 | 4.4 | |
| | 3H | 2.2 | 3.2 | 2.6 | 3.6 | 4.0 | 2.2 | 3.2 | 2.6 | 3.6 | 4.0 | |
| | 4H | 2.1 | 3.1 | 2.5 | 3.5 | 3.9 | 2.1 | 3.1 | 2.5 | 3.5 | 3.9 | |
| | 6H | 1.7 | 3.4 | 2.2 | 3.9 | 4.3 | 1.7 | 3.4 | 2.2 | 3.9 | 4.3 | |
| | 8H | 1.6 | 3.5 | 2.1 | 4.0 | 4.5 | 1.6 | 3.5 | 2.1 | 3.9 | 4.4 | |
| | 12H | 1.5 | 3.5 | 2.0 | 4.0 | 4.5 | 1.5 | 3.5 | 2.0 | 3.9 | 4.5 | |
| 8H | 4H | 1.6 | 3.5 | 2.1 | 3.9 | 4.4 | 1.6 | 3.5 | 2.1 | 4.0 | 4.5 | |
| | 6H | 1.5 | 3.3 | 2.0 | 3.8 | 4.3 | 1.5 | 3.3 | 2.0 | 3.8 | 4.3 | |
| | 8H | 1.5 | 3.1 | 2.0 | 3.6 | 4.1 | 1.5 | 3.1 | 2.0 | 3.6 | 4.1 | |
| | 12H | 1.7 | 2.7 | 2.2 | 3.2 | 3.7 | 1.7 | 2.7 | 2.2 | 3.2 | 3.7 | |
| 12H | 4H | 1.5 | 3.5 | 2.0 | 3.9 | 4.5 | 1.5 | 3.5 | 2.0 | 4.0 | 4.5 | |
| | 6H | 1.5 | 3.1 | 2.0 | 3.6 | 4.1 | 1.5 | 3.1 | 2.0 | 3.6 | 4.1 | |
| | 8H | 1.7 | 2.7 | 2.2 | 3.2 | 3.7 | 1.7 | 2.7 | 2.2 | 3.2 | 3.7 | |
| Variations with the observer position at spacing: | | | | | | | | | | | | |
| S = | | 1.0H | 6.9 / -11.5 | | | | | 6.9 / -11.5 | | | | |
| | | 1.5H | 9.7 / -11.7 | | | | | 9.7 / -11.7 | | | | |
| | | 2.0H | 11.7 / -11.8 | | | | | 11.7 / -11.8 | | | | |