

- 7 (0.3°)	adjustable up to 3000 (10') standard adjustable up to 30500 (100')
C	custom
$\bigcirc$	±140 (5.5*)
116 (4.5*)	

PENDANTS:	one
MOUNTING:	shallow brushed nickel canopy 116mm (4.5") in diameter x 7mm (0.3") deep
LAMPING:	1w LED
COAX:	adjustable. 3000mm (10') standard / up to 30500mm (100') maximum
MATERIALS:	blown glass, copper mesh, braided metal coaxial cable, electrical components brushed nickel canopy
WEIGHT:	approximately 0.7kg (1.5lb)
RANSFORMERS:	integral (transformer housed within junction box). Transformers included

## DESCRIPTION

The 76.1 shallow canopy is a single 76 pendant fixture with a shallow brushed nickel canopy designed to fit over an existing junction box in which the transformer is installed. The canopy is 116mm (4.5") in diameter and 7mm (0.3") deep, which creates a subtle profile that minimizes the impact in the application surface. The pendant drop lengths on this light fixture are adjustable up to the specified maximum.

A vacuum is introduced to a strata composed of hot white and clear glass with copper mesh between. The vacuum causes the white layer to pull away through the embedded mesh, leaving numerous tendrils of white glass suspended within an interstitial space as it goes.

## NOTES

+ Purchase replacement lamps online at www.bocci.ca/lamps

US Patent # D817,524 S EU Design Patent # 002840975-0004-0007



Made in Vancouver, Canada

Vancouver sales@bocci.ca www.bocci.ca


approx 0.7kg (1.5lb)

Berlin europe@bocci.ca www.bocci.ca



76.1 Design by Omer Arbel PRODUCT SPECIFICATION





2

the pendant fixture.

## 1

Very carefully uncoil the braided : Determine the overall drop coaxial cable in a spool like manner. Insert your index fingers into opposite sides of the roll then rotate your fingers around each other to unroll the coaxial cable.

Use patience: allow the cable to uncoil completely to avoid kinks.

•	setscrews strain relief	Line Neutral (black) (white) white (LED) black (LED) black (110V) black (110V) 12V		lamp copper extender	
	3	4	5	6	7
rop for	Thread the coaxial cable through the canopy, use a 2mm Allen key to loosen the setscrew in the canopy and genty feed the cable through until you have reached your desired drop length. Use Allen key to tighten the setscrew to hold the strain relief and secure the coaxial cable at its new length. Perform a gentle tug test to ensure it is secure. DO NOT OVERTIGHTEN. Note: The strain relief is a black plastic collar around the coaxial cable. There is a single slot opening on the side of the strain relief component. It is essential that this opening is oriented at 90 degrees to set screw chamber. There can be no contact between the set screw and the cable. RISK OF ELECTRIC SHORT!	Connect the black wire to black and white wire to white wire. Connect the coaxial cable to the open slots in the terminal block on the 12V side of the transformers. For multiple pendant installations, ensure that the braided outer wires are all connected to one 12V output wire and all inner insulated wires are connected to the other or a short will occur. Once all coaxial connections are made, lift the fixture into position and connect the line voltage to the open slot in the appropriate terminal block.	The client is responsible to ensure fasteners are attached to a robust structural substrate. Tuck the transformer and wiring into the octagonal box, if available, and place canopy over top, lining up the fastener holes or connecting directly to structural ceiling surface. Affix canopy with fasteners provided.	Remove the centre cap from 76 pendant. Install 76 pendant by sliding the lampholder at the end of the coaxial cable into the groove in the pendant hardware. Bocci 1w LED lamps are included. Plug the lamp into flexible copper extender. Hold lamp wires away from the pendant to ensure they do not interfere with spinning cap. Thread centre cap back on to pendant hardware. DO NOT OVERTIGHTEN. Bend the insulated wires and insert the lamp into the small hole in the pendant. Ensure that the lamp does not touch the inner glass bubble.	Clean fingerprints from glass surfaces. Turn fixture on. For additional assistance, please contact Bocci: Vancouver sales@bocci.ca www.bocci.ca Berlin europe@bocci.ca www.bocci.ca US Patent Pending EU Design Patent # 002840975-0004-0007 Made in Vancouver, Canada
					LISTED LOW VOLTAGE LUMINAIRE E476186

SHALLOW CANOPY



