





Type	TWI08-11-8030-TD	<b>TWI08-11-8030-TD</b>
Order No	TWI08-11-8030-TD	
Lamp type/assembly	Standing light	
Version	LED	
Energy efficiency class	A+	
Light source	LED, CRI > 80	<b>DESIGN PLUS</b>
Colour temperature	2700 - 4000 K	
Operating mode	Dimmable + white tone modulation	
Operation	Cable integrated	
Lamp shade	Acrylic glass, prismatic	
Base	Stainless steel	
Power cable	Black, 3 x 0.75 mm <sup>2</sup> , L 4000 mm	
Mains plug	Swiss T12 (type J)	
Light distribution	Direct (2090 lm) / indirect (2630 lm)	
Total luminous flux of luminaire	4720 lm	
Power consumption	60 W	
Luminaire efficacy	79 lm/W	
Mains voltage	220-240V / 50Hz	
Stand-by consumption	< 0.5W	
Safety class	I	
Protection type	IP 20	
Packaging units	2 (1980 x 420 x 360 + 1930 x 340 x 270 mm)	
Weight	23.0 kg	
Guarantee	36 months	
Belux Express	Shipping within 5 days of ordering (available for order quantities up to 10 units and subject to availability)	



**Belux AG**  
 Neufeldweg 6, CH-5103 Möriken  
 Tel. +41 61 316 74 01  
 Fax +41 61 316 75 99  
 www.belux.com  
 belux@belux.com

[www.belux.com/twilight](http://www.belux.com/twilight)