

Products /  **CASTALDI** / D63 ATON / D63 ATON / D63C/T00-LBF

## D63 ATON D63C/T00-LBF

### TECHNICAL DATA

#### GENERAL




Item code	D63C/T00-LBF
Place installation	outdoor
Name	D63 ATON / D63C/T00-LBF ceiling recessed
Note	Suitable for use in dropped or drywall ceilings, thickness >1mm.
Standard colour	stainless steel frame sandblasted
Environments	wellness, hallway, leisure areas




#### PHYSICAL

Installation type	ceiling recessed
Mounting type	with rough-in housing
Screws	AISI 304 stainless steel screws.
Seals	Silicone Rubber.
Temperature glass	40°C
Body	Corrosion resistant die-cast aluminium body. AISI 316 stainless steel trim satin finish.



#### DIMENSIONS


D: Total diameter device (mm)	45
Built-in shaped	Round
Diameter built-in (mm)	80
Built-in depth (mm)	75



Ø 39  
dimensioni foro per incasso  
hole dimension for ceiling


#### OPTICAL SYSTEMS

Opening beam	diffused
Optical System	Tempered safety glass, mechanical and thermal shock resistant.



## ENERGY SAVING

This luminaire contains built-in LED lamps  
The lamps cannot be changed in the luminaire



## SOURCES

Source Type	Source Power	System Power	Source	Lamp Socket	Sources Temperature Colour	Nominal Flux	Output Flux	Source description
LED	1x1W	-	Blue LED	-	-	1x28 lm	-	-

## ELECTRICAL

Ballast type	Electronic
Mounting ballast type	Remote
Line input	Pre-wired and tested with resin sealed watertight RN8-F 48V cable (for a fast and secure connection to the main power line, use ACS/CR1 connector or similar).
Voltage	12-24V-DC
Wiring	SELV power supply required, 12-24V-DC.

## NORMS / DIRECTIVES

Norms	EN 60598-1, EN 60598-2-13
Directives	2014/35/UE, 2014/30/UE

## ACCESSORIES

## OPTIONAL ACCESSORIES

### Electrical

<b>Accessory code</b>	<b>ACS/AR15-24</b>
<b>Technical description</b>	For all models D41-D42-D44 tellux/00 and D63 aton. SELV power supply 15W 220/240V-50/60Hz output 24V-DC PWM. Insulation class II, can feed up to 6 tellux.



<b>Accessory code</b>	<b>ACS/CR1</b>
<b>Technical description</b>	Fast IP68 connector 1bar (10m-1h) for cable Ø7-12mm - 3x1.5mm.

