

Products /  CASTALDI / D63 ATON / D63 ATON / D63C/T00-LWWP


D63 ATON D63C/T00-LWWP

TECHNICAL DATA

GENERAL




Item code	D63C/T00-LWWP
Place installation	outdoor
Name	D63 ATON / D63C/T00-LWWP ceiling recessed
Note	Suitable for use in dropped or drywall ceilings, thickness >1mm.
Standard colour	stainless steel frame sandblasted
Environments	wellness, hallway, leisure areas




PHYSICAL

Installation type	ceiling recessed
Mounting type	with rough-in housing
Screws	AISI 304 stainless steel screws.
Seals	Silicone Rubber.
Temperature glass	40°C
Body	Corrosion resistant die-cast aluminium body. AISI 316 stainless steel trim satin finish.



DIMENSIONS


D: Total diameter device (mm)	45
Built-in shaped	Round
Diameter built-in (mm)	80
Built-in depth (mm)	75



Ø 39
dimensioni foro per incasso
hole dimension for ceiling


OPTICAL SYSTEMS

Opening beam	diffused
Optical System	Tempered safety glass, mechanical and thermal shock resistant.



ENERGY SAVING

This luminaire contains built-in LED lamps
The lamps cannot be changed in the luminaire



SOURCES

Source Type	Source Power	System Power	Source	Lamp Socket	Sources Temperature Colour	Nominal Flux	Output Flux	Source description
LED	1x1W	-	Warm White LED	-	3000K	1x100 lm	-	-

ELECTRICAL

Ballast type	Electronic
Mounting ballast type	Remote
Line input	Pre-wired and tested with resin sealed watertight RN8-F 48V cable (for a fast and secure connection to the main power line, use ACS/CR1 connector or similar).
Voltage	12-24V-DC
Wiring	SELV power supply required, 12-24V-DC.

NORMS / DIRECTIVES

Norms	EN 60598-1, EN 60598-2-13
Directives	2014/35/UE, 2014/30/UE

ACCESSORIES

OPTIONAL ACCESSORIES

Electrical

Accessory code	ACS/AR15-24
Technical description	For all models D41-D42-D44 tellux/00 and D63 aton. SELV power supply 15W 220/240V-50/60Hz output 24V-DC PWM. Insulation class II, can feed up to 6 tellux.



Accessory code	ACS/CR1
Technical description	Fast IP68 connector 1bar (10m-1h) for cable Ø7-12mm - 3x1.5mm.

