Product data sheet


Date: October 6th 2021



ABOUT PHILAE SUSPENSION

by Jan Pauwels

Autumn storm, falling leaves, make any combination you like. By playing with the length of the cables, and the number and sizes, you create your own lighting installation. The circuit boards have leds on both sides. 2/3 of the light is going downwards and 1/3 is going upwards



	INSIONS	LIGHTSOURCE
	85 cm 33.5 inch	29 x 12V/0,6W, 2800K
н	10 cm 39 inch	29 x 120/0,600, 2800K, 870LM, CRI 95
W	42 cm 16.5 inch	670LM, CRI 95
vv	42 CH1 10.3 INCH	
		INCLUDED
CAN	OPY	Yes
L	28 cm 11 inch	
Н	4.5 cm 1.8 inch	
W	10 cm 3.9 inch	KG
		3 6 96x51x17

CABLELENGTH Up to 200 cm 78 inch

29 x 12V/0,6W, 2800K,		
870LM, CRI 95		
INCLUDED		
Yes		





Nickel Brass Copper

TYPE	suspension
STANDARD	The fixture is supplied with a black canopy with cover plate in matching colour of the fixture. Leading and trailing edge dimmable.
OPTIONAL	Dim unit with remote control (other dimming options on request).
TRANSFORMER/DRIVER	SCPower KVF-12030-TDW
DIMMING	leading and trailing edge

ENERGY LABEL

YEAR OF DESIGN

UL no IP20 yes

2016

Quasar Holland BV®

Burgstraat 2 4283GG Giessen The Netherlands T. +31-(0)183-447887 F. +31-(0)183-448337 export@quasar.nl www.quasar.nl