

## Q-BO CEILING

1V7374SI

LIGHT SOURCE **QT-DE12 (74,9)/LED R7s** SOCKET **R7s** POWER (SOURCE) **max 120W/7W** EMISSION **DIRECT**  
 COLOUR AND FINISH **SILVER** VERSION **LARGE** SIZE **AxBxH=135x135x135mm** POWER SUPPLY **220-240Vac 50/60Hz**  
 POWER SUPPLY TYPE **CONSTANT VOLTAGE** INSULATION CLASS **CLASS 1** GLOBAL IP OR HOUSING **IP20** F CLASS **YES**  
 LIGHT EFFECTS **FLOOD LIGHTING**



### CONCEPT

Ceiling mounted fixture with direct light emission for halogen and LED lamp.

### MATERIALS

Body made of painted extruded aluminium.

### INSTALLATION


Supplied as standard without screens, which are available as accessories.

### POWER SUPPLY

220-240Vac 50/60Hz

### NOTES

Casambi control system available by using a dedicated accessory (Halogen version - constant voltage max 150W). To ensure the Q-BO LED version works correctly we recommend you use the accessory sources contained in this catalogue. Non-dimmable LED R7s lamp.



All the measures are expressed in mm

## Photometries

| 3000K Ra100   |                             | H(m) | D(m)  | Emax(lx) |
|---------------|-----------------------------|------|-------|----------|
| Fixture Power | 120W                        |      | 114°  |          |
| Source Flux   | 2220lm                      | 1    | 3.06  | 240      |
| Fixture Flux  | 686lm                       | 2    | 6.12  | 60       |
| Efficacy      | 6lm/W                       | 3    | 9.18  | 27       |
|               |                             | 4    | 12.24 | 15       |
|               |                             | 5    | 15.30 | 10       |
| VI081         | I <sub>max</sub> =108cd/klm |      |       |          |

## Accessory Codes

### Optical



#### L1970N

---

##### Source

LED R7s 7W (4000K) 800lm R7s.  
230V



#### L1970W

---

##### Source

LED R7s 7W (2700K) 750lm R7s.  
230V



#### 1V7364SI

---

##### Shaper

Plate with central slot for light-blade effect. Large version IP40. Silver.



#### 1V7360SI

---

##### Glass

Frame with sandblasted glass. Large version IP40. Silver.

### Control Systems



#### 1T5351

---

##### Control System

A Wireless Trailing Edge / IGBT dimmer managed using Bluetooth 4.0 technology. It works with LED 230 V-AC modules, dimmable LED sources and halogen lamps. It can be installed inside a standard 503 wall switch box, lighting fixtures or ceiling canopies. It can manage systems with a maximum absorption of 150W. The module is wireless controlled using a CASAMBI app for smartphones and tablets or traditional wall switches. IP20