

## MONETA CEILING

1T3765

LIGHT SOURCE **LED** COLOUR TEMPERATURE **3000K** POWER (SOURCE) **18W** CRI **80** BEAM ANGLE **VWFL**  
 COLOUR AND FINISH **PLASTER WHITE** POWER SUPPLY **220-240Vac 50/60Hz** INSULATION CLASS **CLASS 2**  
 GLOBAL IP OR HOUSING **IP40** F CLASS **YES**



### CONCEPT

Direct emission ceiling and wall mounted dimmable LED fixture.

### MATERIALS

Matt painted aluminium body complete with opaline polycarbonate diffuser.

### SOURCE

Dimmable LED module 230V.

### OPTIC


Metalised aluminium internal reflector.

### POWER SUPPLY

Driver not required. 220-240Vac 50/60Hz

### NOTES

Casambi control system available by using a dedicated accessory (230Vac LED module max 150W).



All the measures are expressed in mm

## Photometries

| 3000K Ra80    |                             | H(m) | D(m)  | E <sub>max</sub> (lx) |
|---------------|-----------------------------|------|-------|-----------------------|
| Fixture Power | 18W                         |      | 115°  |                       |
| Source Flux   | 826lm                       | 1    | 3.15  | 281                   |
| Fixture Flux  | 826lm                       | 2    | 6.31  | 70                    |
| Efficacy      | 46lm/W                      | 3    | 9.46  | 31                    |
|               |                             | 4    | 12.62 | 18                    |
|               |                             | 5    | 15.77 | 11                    |
| TS771         | I <sub>max</sub> =341cd/klm |      |       |                       |
|               | I <sub>max</sub>            |      |       | 281cd                 |

---

## Accessory Codes

### Control Systems



#### **1T5351**

---

##### **Control System**

A Wireless Trailing Edge / IGBT dimmer managed using Bluetooth 4.0 technology. It works with LED 230 V-AC modules, dimmable LED sources and halogen lamps. It can be installed inside a standard 503 wall switch box, lighting fixtures or ceiling canopies. It can manage systems with a maximum absorption of 150W. The module is wireless controlled using a CASAMBI app for smartphones and tablets or traditional wall switches. IP20