

## MONETA CEILING

1T3765FE

LIGHT SOURCE **LED** COLOUR TEMPERATURE **3000K** POWER (SOURCE) **18W** CRI **80** BEAM ANGLE **VWFL**

COLOUR AND FINISH **FERRITE** POWER SUPPLY **220-240Vac 50/60Hz** INSULATION CLASS **CLASS 2**

GLOBAL IP OR HOUSING **IP40** F CLASS **YES**



### CONCEPT

Direct emission ceiling and wall mounted dimmable LED fixture.

### MATERIALS

Matt painted aluminium body complete with opaline polycarbonate diffuser.

### SOURCE

Dimmable LED module 230V.

### OPTIC


Metalised aluminium internal reflector.

### POWER SUPPLY

Driver not required. 220-240Vac 50/60Hz

### NOTES

Casambi control system available by using a dedicated accessory (230Vac LED module max 150W).



All the measures are expressed in mm

## Photometries

3000K Ra80		H(m)	D(m)	E <sub>max</sub> (lx)
Fixture Power	18W		115°	
Source Flux	826lm	1	3.15	281
Fixture Flux	826lm	2	6.31	70
Efficacy	46lm/W	3	9.46	31
		4	12.62	18
		5	15.77	11
TS771	I <sub>max</sub> =341cd/klm			
	I <sub>max</sub>			281cd

---

## Accessory Codes

### Control Systems



#### **1T5351**

---

##### **Control System**

A Wireless Trailing Edge / IGBT dimmer managed using Bluetooth 4.0 technology. It works with LED 230 V-AC modules, dimmable LED sources and halogen lamps. It can be installed inside a standard 503 wall switch box, lighting fixtures or ceiling canopies. It can manage systems with a maximum absorption of 150W. The module is wireless controlled using a CASAMBI app for smartphones and tablets or traditional wall switches. IP20