

MONETA CEILING

1T3765GO

LIGHT SOURCE **LED** COLOUR TEMPERATURE **3000K** POWER (SOURCE) **18W** CRI **80** BEAM ANGLE **VWFL**

COLOUR AND FINISH **GOLD** POWER SUPPLY **220-240Vac 50/60Hz** INSULATION CLASS **CLASS 2**

GLOBAL IP OR HOUSING **IP40** F CLASS **YES**



CONCEPT

Direct emission ceiling and wall mounted dimmable LED fixture.

MATERIALS

Matt painted aluminium body complete with opaline polycarbonate diffuser.

SOURCE

Dimmable LED module 230V.

OPTIC


Metalised aluminium internal reflector.

POWER SUPPLY

Driver not required. 220-240Vac 50/60Hz

NOTES

Casambi control system available by using a dedicated accessory (230Vac LED module max 150W).



All the measures are expressed in mm

Photometries

3000K Ra80		H(m)	D(m)	E _{max} (lx)
Fixture Power	18W		115°	
Source Flux	826lm	1	3.15	281
Fixture Flux	826lm	2	6.31	70
Efficacy	46lm/W	3	9.46	31
		4	12.62	18
		5	15.77	11
TS771	I _{max} =341cd/klm			
	I _{max}			281cd

Accessory Codes

Control Systems



1T5351

Control System

A Wireless Trailing Edge / IGBT dimmer managed using Bluetooth 4.0 technology. It works with LED 230 V-AC modules, dimmable LED sources and halogen lamps. It can be installed inside a standard 503 wall switch box, lighting fixtures or ceiling canopies. It can manage systems with a maximum absorption of 150W. The module is wireless controlled using a CASAMBI app for smartphones and tablets or traditional wall switches. IP20