

XGR1021 - XGR1021

Lighting fixture for ceiling or wall built-in installation for interiors, with direct light emission.

Total built-in plaster structure for masonry or plasterboard.

Light source retaining spring clip in stainless steel.

Fixing brackets in micro-perforated sheet metal.

Recessed housing for masonry in galvanized sheet metal to be ordered separately.

Built-in hole dimension: 140x140mm (5,5x5,5")

DATA SHEET



Code	XGR1021
System power consumption	max 50W
Light source	LED retrofit halogen
Light source kit	not included
Power supply	220-240V AC
Frequency	50/60Hz
Weight	0,4150Kg
Protection degree	IP20
Dimensions	19 x 11 x 15



ACCESSORIES

XM2
GU5,3 lampholder, cable and terminal block kit.
GU5,3 / max 50W
12V AC

XM5/250 HO
LED lamp 8,5W 250mA 34V 3000K Ra>80 990lm 48°. LED / LED / 8,5W / wide flood / 3000K Ra >80 250mA DC

XM5/350N
LED lamp 6,8W 350mA 19,4V 3000K Ra>80 503lm 43°. LED / LED / 6,8W / wide flood / 3000K Ra >80 350mA DC

XM1021
Galvanized sheet housing to be recessed in brick walls or concrete.

XM6-20 D/P MULTI
LED driver, 9,2÷20,4W 200÷900mA, 1-10V/DALI/Push DIM dimmable.

XM6-25 D/P MULTI
LED driver, 8,4÷25,6W 150÷900mA, DALI/Push DIM dimmable.

XM6/250/10
LED driver, 10W 250mA.

XM6/350/12
LED driver, 12W 350mA.

XMGU10
PAR16 LED lamp GU10 9W 110-240V AC 3000K Ra>80 840lm 36°, not dimmable.
LED retrofit / GU10 / 9W / 840lm / 3000K Ra >80
110-240V AC / 50/60Hz / ON-OFF

 Colour
plaster



 TECHNICAL DRAWING



