

QUALITY MARKS



There are no colors for the product.

OCEAN SPOT

Outdoor and indoor spotlight with adjustable optical group constructed of:


- Stainless steel AISI 316L body
- Stainless steel AISI 304 fixing bracket
- Tempered glass
- 10°, 45°, 90° optics
- Neoprene cable L 500 mm
- Silicon gaskets
- Stainless steel AISI 304 spike

NOTES


Distance between driver and spotlight: max 20 mt
Available with 10°, 45°, 90° optics

Code	Light source	Power	Lum. Flux *	Colour Temperature	Beam angle
4310.66.10X	LED CRI85	3W	320 lm	4000 K	10°
4310.66.45X	LED CRI85	3W	320 lm	4000 K	45°
4310.66.90X	LED CRI85	3W	320 lm	4000 K	90°
4310.67.10X	LED CRI85	3W	300 lm	2700 K	10°
4310.67.45X	LED CRI85	3W	300 lm	2700 K	45°
4310.67.90X	LED CRI85	3W	300 lm	2700 K	90°


* Lumen rating is related to the flux emitted by the LED module and not to the flux emitted by the appliance




Floor mounting



Operating temperature -40°C
+50°C




Single power supply cables
input




LED:
The luminaire needs a remote
power supply (supplied only on
request)



Impact Energy (J):
20



cod. A10:



PQ 51:
ACCESSORY (on request)
Stainless steel AISI 304 ground spike.