

100% Suspension Basic - Silver/white



DESIGN BY


Ross Lovegrove

DESCRIPTION

Only 6mm of thickness of the aluminum body. Controlled direct and indirect diffuse emission. Touch dimmer on the module body (Only for 100% Suspension). Independent management of each module even within multiple configurations (Only for 100% Suspension). It is possible to connect up to 7 modules with a single power supply. Mechanical connecting elements (Magnetic) and electrical on the edges of each module. Connection joints 90 ° and 120 °.

IP20 ⊕





FFATURES

FEATURES			
Article Code: Colour: Installation: Environment:	DRL1903B00B Silver/white Suspension Indoor	Series:	Scenarios
DIMENSIONS			
Length: Width: Height: Weight:	cm 120 cm 0.6 cm 10 kg 1.6		
INCLUDED SOURCES			
Category: Number: Watt: Type: Class:	LED 1 32W 0 A	Color temperature (K):	3000K

LUMINAIRE

 Watt:
 32W
 Delivered lumens output (Im): 2427lm

 CCT:
 4000K

 Efficiency:
 80%

 Efficacy:
 75.84lm/W

 CRI:
 80



ACCESSORIES



100% - 90° Connector Silver/white DRL1903AKTC100B



100% - Power supply kit 120W 2/4 modules Silver/white DRL1903AKB02



100% - 120° Connector Silver/white DRL1903AKTC200B



100% - Power supply kit 320W 5/7 modules Silver/white DRL1903AKC02



100% - Power supply kit 40W 1 module Silver/white DRL1903AKA02



100% - Terminal head White DRL1903ATPC10



100% - Terminal head Silver DRL1903ATPC00