


A.24 - Ceiling Sharping Emission - Curved Elements - 62° - R=750mm - α=90° - 2700K - Black



IP20   Dimmerable: 


DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

A.24 is an open platform. A single intelligent profile generates three light performances while following the architecture with continuity, freedom and exibility. It is a fluid system that harbours a patented optoelectronic technology.

TECHNICAL DRAWINGS



FEATURES

| | | | |
|----------------------|--|------------------|---------------------|
| Article Code: | AQ63904 | Series: | Indoor, 2018 |
| Colour: | Black | Emission: | Artemide Collection |
| Installation: | Recessed, Wall, Suspension, Ceiling | | Direct |
| Environment: | Indoor | | |

DIMENSIONS

| | |
|----------------|--------|
| Width: | cm 2.7 |
| Height: | cm 5.4 |

INCLUDED SOURCES

| | | | |
|------------------|-----|-------------------------------|-----------------|
| Category: | LED | Color temperature (K): | 2700K |
| Number: | 1 | Color Tolerance: | MacAdam 2SDCM |
| Watt: | 25W | Service Life: | L70 (6K) 50000h |
| Type: | 0 | | |

LUMINAIRE

| | | | |
|--------------|-----|--------------------------------------|--------|
| Watt: | 25W | Delivered lumens output (lm): | 1555lm |
| | | CCT: | 2700K |
| | | CRI: | 90 |

Notes

*Uses 1 DALI address. Each module, angle and curved elements are provided with mechanical and electrical joints and installation accessories. Bracket for fixing to ceiling is included: 1 for 1176mm length - 2 for 2352 mm length. End caps have to be ordered separately. Sharping kit (louvres and covers) has to be ordered separately. Depending on the driver, the product can be undimmable or dimmable DALI.

ACCESSORIES



150W Ceiling power supply kit - 351x61x111H - 230VAC-48VDC IP20 - Undimmable - White AQ17901



150W Ceiling power supply kit - 351x61x111H - 230VAC-48VDC IP20 - Undimmable - Black AQ17904



240W Bare power supply + plug 230VAC-48VDC IP20 - Undimmable (for dimmable version to be combined with "DALI-Selv interface") AQ18000




150W Bare power supply + plug 230VAC-48VDC IP20 - Undimmable (for dimmable version to be combined with "DALI-Selv interface") AQ18100




240W Ceiling power supply kit - 321x91x111H - 230VAC-48VDC IP20 - Dimmable DALI - White AQ17201



Cap for cable - Black AQ35304



240W Ceiling power supply kit - 321x91x111H - 230VAC-48VDC IP20 - Dimmable DALI - Black AQ17204




A.24 - Flexible Cover L=10m - Black AQ92004



A.24 - Remote Box Power Supply Kit - 313x243x57,5h - (230VAC-48VDC 240W DALI) AQ16000



240W Recessed power supply kit - 396x195x112H - 230VAC-48VDC IP20 - DALI AQ16801



A.24 - Insulating Spacer (1x) - Black AQ35204



240W Recessed power supply kit - 396x195x112H - 230VAC-48VDC IP20 - Undimmable AQ17801




240W Ceiling power supply kit - 351x61x111H - 230VAC-48VDC IP20 - Undimmable - White AQ17301



240W Ceiling power supply kit - 351x61x111H -



A.24 - Wall/Ceiling Accessories - Transition Cap -



A.24 - Louver for Curved Elements - White (Order 1pc


230VAC-48VDC
IP20 -
Undimmable -
Black
AQ17304

Black
AQ39404

for R=561 60°/90°
R=750 45°, 2 pcs
for R=750 90°)
AQ91101




A.24 - Louver for
Curved Elements
- Black (Order 1 pc
for R=561 60°/90°
R=750 45°, 2 pcs
for R=750 90°)
AQ91104



A.24 - Flexible
Cover L=10m -
White
AQ92001



150W Ceiling
power supply kit -
321x91x111H -
230VAC-48VDC
IP20 - Dimmable
DALI - White
AQ17701



A.24 - Wall/Ceiling
Accessories - End
Cap (2x) - Black
AQ35004




150W Ceiling
power supply kit -
321x91x111H -
230VAC-48VDC
IP20 - Dimmable
DALI - Black
AQ17704



A.24 - Flexible
Cover L=2m -
White
AQ92101



A.24 - Flexible
Cover L=2m -
Black
AQ92104



DALI to DALI-Selv
Interface
103x67x21H
AQ18200