PRODUCT DATA SHEET PRODUCT CODE: AQ32518

A.24 - Ceiling Sharping Emission - Track - Direct Emission - 2352mm - 24° - 2700K - Brushed Copper




DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

A.24 is an open platform. A single intelligent profile generates three light performances while following the architecture with continuity, freedom and exibility. It is a fluid system that harbours a patented optoelectronic technology.



FEATURES

Colour: Brust Installation: Reconstruction Susy Environment: Indo DIMENSIONS Length: cm : Width: cm : Height: cm :	shed Copper	Series:	Indoor, 2018 Artemide Collection
Installation: Recc Susy Environment: Indo			Artemide Collection
Suspension DIMENSIONS Length: cm: Width: cm: Height: cm:	essed, Wall,		
Environment: Indo		Emission:	Direct
DIMENSIONS Length: cm : Width: cm : Height: cm :	pension, Ceiling		
Length: cm : Width: cm : Height: cm :	oor		
Length: cm : Width: cm : Height: cm :			
Width: cm 2 Height: cm 3			
Height: cm !	235.2		
	2.7		
<u> </u>	5.4		
Weight: kg 2	2.7		
INCLUDED SOURCES			
Category: LED	ı	Color temperature (K):	2700K
Number: 1		Color Tolerance:	MacAdam 2SDCM
Watt: 50W	V	Service Life:	L70 (6K) 50000h
Type: 0			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
-76			
LUMINAIRE			

Notes

Watt:

*Uses 2 DALI addresses. Each module, angle and curved elements are provided with mechanical and electrical joints and installation accessories. Bracket for fixing to ceiling is included: 1 for 1176mm length - 2 for 2352 mm length. End caps have to be ordered separately. Sharping kit (louvres and covers) has to be ordered separately. Depending on the driver, the product can be undimmable or dimmable DALI.

CCT:

CRI:

Delivered lumens output (lm): 3056lm

2700K

50W

ACCESSORIES



150W Ceiling power supply kit -351x61x111H -230VAC-48VDC IP20 -Undimmable -White AQ17901

150W Bare power

supply + plug

IP20 -

230VAC-48VDC

Undimmable (for

dimmable version

to be combined

with "DALI-Selv interface") AQ18100



150W Ceiling power supply kit -351x61x111H -230VAC-48VDC IP20 -Undimmable -Black AQ17904



240W Bare power supply + plug 230VAC-48VDC IP20 -Undimmable (for dimmable version to be combined with "DALI-Selv interface") AQ18000



240W Ceiling power supply kit -321x91x111H -230VAC-48VDC IP20 - Dimmable DALI - White AQ17201



240W Ceiling power supply kit -321x91x111H -230VAC-48VDC IP20 - Dimmable DALI - Black AQ17204



A.24 - Remote Box Power Supply Kit -313x243x57.5h -(230VAC-48VDC 240W DALI) AQ16000



240W Recessed power supply kit -396x195x112H -230VAC-48VDC IP20 - DALI AQ16801



240W Ceiling power supply kit -351x61x111H -230VAC-48VDC IP20 -Undimmable -White AQ17301



240W Ceiling power supply kit -351x61x111H -230VAC-48VDC IP20 -Undimmable -Black AQ17304



A.24 - Wall/Ceiling Accessories -Transition Cap -Brushed copper AQ39418 150W Ceiling power supply kit -321x91x111H -230VAC-48VDC



240W Recessed power supply kit -396x195x112H -230VAC-48VDC IP20 -Undimmable AQ17801



A.24 - Sharping Kit L=2352mm - Black AQ26104







Cap for cable -

A.24 - Wall/Ceiling

Accessories - End

Cap (2x) - Brushed

Copper

AQ35018

AQ35318

NO IMAGE AVAILABLE

A.24 - Insulating Spacer (1x) -Brushed Copper AQ35218 DALI - White AQ17701



DALI to DALI-Selv Interface 103x67x21H AQ18200

DALI - Black AQ17704



A.24 - Sharping Kit L=2352mm -White AQ26101