


A.24 - Recessed Sharping Emission - Curved Elements - 62° - R=561mm - α =60° - 3000K - White





| FEATURES | | | |
|--|--|--------------------------------|---------------------|
| Article Code: | AQ50401 | Series: | Indoor, 2018 |
| Colour: | White | | Artemide Collection |
| Installation: | Recessed, Wall, Suspension, Ceiling | Emission: | Direct |
| Environment: | Indoor | | |
| DIMENSIONS | | | |
| | | | |
| Width: | cm 2.7 | | |
| Width: Recessed depth: | cm 2.7 cm 5.4 | | |
| Recessed depth: | | | |
| Recessed depth: | cm 5.4 | Color tomorrative ///) | 2000/ |
| Recessed depth: INCLUDED SOURCES Category: | cm 5.4 LED | Color temperature (K): | 3000K |
| Recessed depth: INCLUDED SOURCES Category: Number: | cm 5.4 LED 1 | Color temperature (K): CRI: | 3000К 90 |
| Recessed depth: INCLUDED SOURCES Category: Number: Watt: | cm 5.4 LED | • | |
| Recessed depth: INCLUDED SOURCES Category: Number: | cm 5.4 LED 1 12W | • | |
| Recessed depth: INCLUDED SOURCES Category: Number: Watt: | cm 5.4 LED 1 12W | • | |
| Recessed depth: INCLUDED SOURCES Category: Number: Watt: Type: | cm 5.4 LED 1 12W | • | 90 |
| Recessed depth: INCLUDED SOURCES Category: Number: Watt: Type: LUMINAIRE | cm 5.4 LED 1 12W 0 | CRI: | 90 |

*Uses 1 DALI address. Each module, angle and curved elements are provided with mechanical and electrical joints and installation accessories. End caps have to be ordered separately. Sharping kit (louvres and covers) has to be ordered separately. Depending on the driver, the product can be undimmable or dimmable DALI.

IP20 (Dimmerable: +)-

DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

A.24 is an open platform. A single intelligent profile generates three light performances while following the architecture with continuity, freedom and exibility. It is a fluid system that harbours a patented optoelectronic technology.



PRODUCT CODE: AQ50401

ACCESSORIES



150W Ceiling power supply kit -351x61x111H -230VAC-48VDC IP20 -Undimmable -White AQ17901



150W Bare power supply + plug 230VAC-48VDC IP20 -Undimmable (for dimmable version to be combined with "DALI-Selv interface") AQ18100



150W Ceiling power supply kit -351x61x111H -230VAC-48VDC IP20 -Undimmable -Black AQ17904



240W Ceiling power supply kit -321x91x111H -230VAC-48VDC IP20 - Dimmable DALI - White AQ17201



A.24 - Flexible Cover L=10m -Black AQ92004



240W Recessed power supply kit -396x195x112H -230VAC-48VDC IP20 - DALI AQ16801



240W Ceiling power supply kit -351x61x111H -230VAC-48VDC IP20 -Undimmable -Black AQ17304



240W Bare power supply + plug 230VAC-48VDC IP20 -Undimmable (for dimmable version to be combined with "DALI-Selv interface") AQ18000



240W Ceiling power supply kit -321x91x111H -230VAC-48VDC IP20 - Dimmable DALI - Black AQ17204



A.24 - Recessed Accessories -Transition Joint -White AQ29001



240W Recessed power supply kit -396x195x112H -230VAC-48VDC IP20 -Undimmable AQ17801



A.24 - Louver for Courved Elements - R=561mm -White AQ91001



A.24 - Louver for Courved Elements - R=561mm - Black

March 2019



A.24 - Remote Box Power Supply Kit -313x243x57,5h -(230VAC-48VDC 240W DALI) AQ16000



240W Ceiling power supply kit -351x61x111H -230VAC-48VDC IP20 -Undimmable -White AQ17301

AQ91004



A.24 - Flexible Cover L=10m -White AQ92001



Accessories -Insulating Spacer (1x) - White AQ24101



150W Ceiling power supply kit -321x91x111H -230VAC-48VDC IP20 - Dimmable DALI - White AQ17701



DALI to DALI-Selv Interface 103x67x21H AQ18200



A.24 - Recessed Accessories - End Cap (2x) - White AQ25001



150W Ceiling power supply kit -321x91x111H -230VAC-48VDC IP20 - Dimmable DALI - Black AQ17704