

A.24 - Suspension Diffused Emission - Track - Direct Emission - 2352mm - 2700K - Brushed Bronze




IP20 Dimmerable:

DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

TECHNICAL DRAWINGS



FEATURES

Article Code:	AQ41720	Series:	Indoor, 2018
Colour:	Brushed Bronze	Emission:	Artemide Collection Direct
Installation:	Recessed, Wall, Suspension, Ceiling		
Environment:	Indoor		

DIMENSIONS

Length:	cm 235.2
Width:	cm 2.7
Weight:	kg 2.7
Recessed depth:	cm 5.4

INCLUDED SOURCES

Category:	LED	Color temperature (K):	2700K
Number:	1	Color Tolerance:	MacAdam 2SDCM
Watt:	66W	Service Life:	L70 (6K) 50000h
Type:	0		

LUMINAIRE

Watt:	66W	Delivered lumens output (lm):	5683lm
		CCT:	2700K
		CRI:	80

Notes

*Uses 2 DALI addresses. Each module, angle and curved elements are provided with mechanical and electrical joints and installation accessories. 1 suspension cable is also included. End caps have to be ordered separately. Opal diffusing screen has to be ordered separately. Depending on the driver, the product can be undimmable or dimmable DALI.


ACCESSORIES



Suspension Accessories - Recessed Power Supply Kit For Suspension Modules (230VAC-48VDC 240W DALI) - Black
AQ15404



A.24 - Suspension Accessories - Ceiling Power Supply Kit For Suspension Modules (230VAC-48VDC 240W DALI) - White
AQ16101



A.24 - Suspension Accessories - Ceiling Power Supply Kit For Suspension Modules (230VAC-48VDC 240W DALI) - Black
AQ16104




A.24 - Remote Box Power Supply Kit - 313x243x57,5h - (230VAC-48VDC 240W DALI)
AQ16000



A.24 - Opal Diffusing Screen - 10m
AQ16200




Suspension Accessories - Recessed Power Supply Kit For Suspension Modules (230VAC-48VDC 240W DALI) - White
AQ15401




240W Bare power supply + plug 230VAC-48VDC IP20 - Undimmable (for dimmable version to be combined with "DALI-Selv interface")
AQ18000




150W Bare power supply + plug 230VAC-48VDC IP20 - Undimmable (for dimmable version to be combined with "DALI-Selv interface")
AQ18100




A.24 - Opal Diffusing Screen - 25m
AQ16300




A.24 - Opal Diffusing Screen - 2352mm
AQ16600




A.24 - Opal Diffusing Screen - 3528mm
AQ16700



A.24 - Flexible Opal Diffusing Screen - 10m
AQ90000



A.24 - Flexible Opal Diffusing Screen - 25m
AQ90100




A.24 - Flexible Opal Diffusing Screen - 50m
AQ90200



240W Ceiling power supply kit - 351x61x111H - 230VAC-48VDC IP20 - Undimmable - Black



150W Ceiling power supply kit - 351x61x111H - 230VAC-48VDC IP20 - Undimmable - White
AQ17601



A.24 - Suspension Accessories - End Cap (2x) - Brushed Bronze
AQ45120




150W Ceiling power supply kit - 351x61x111H - 230VAC-48VDC IP20 - Undimmable - Black
AQ17604



150W Ceiling power supply - kit 321x91x111H - 230VAC-48VDC IP20 - Dimmable DALI - White
AQ17501



150W Ceiling power supply - kit 321x91x111H - 230VAC-48VDC IP20 - Dimmable DALI - Black
AQ17504



DALI to DALI-Selv Interface 103x67x21H
AQ18200



A.24 - Suspension Accessories - Transition Cap - Brushed bronze
AQ49420



240W Recessed power supply kit - 396x195x112H - 230VAC-48VDC IP20 - Undimmable - White
AQ17401



240W Recessed power supply kit - 396x195x112H - 230VAC-48VDC IP20 - Undimmable - Black
AQ17404



240W Ceiling power supply kit - 351x61x111H - 230VAC-48VDC IP20 - Undimmable - White
AQ17101



A.24 - Suspension Accessories - Insulating Spacer (1x) - Brushed Bronze
AQ45220