PRODUCT DATA SHEET PRODUCT CODE: AQ48620

A.24 - Suspension Sharping Emission - Track - Direct + Indirect Emission - 1176mm - 62° - 2700K - Brushed Bronze




DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

 $A.24\,is\,an\,open\,platform.\,A\,single\,intelligent\,profile\,generates\,three\,light\,performances\,while\,following\,the$ architecture with continuity, freedom and exibility. It is a fluid system that harbours a patented

TECHNICAL DRAWINGS



| FEATURES | | | |
|------------------|--|------------------------|---------------------|
| Article Code: | AQ48620 | Series: | Indoor, 2018 |
| Colour: | Brushed Bronze | | Artemide Collection |
| Installation: | Recessed, Wall, Suspension, Ceiling | Emission: | Direct |
| Environment: | Indoor | | |
| DIMENSIONS | | | |
| Length: | cm 117.6 | | |
| Width: | cm 2.7 | | |
| Height: | cm 5.4 | | |
| Weight: | kg 1.4 | | |
| INCLUDED SOURCES | | | |
| Category: | LED | Color temperature (K): | 2700K |
| Number: | 1 | Color Tolerance: | MacAdam 2SDCM |
| Watt: | 16W | Service Life: | L70 (6K) 50000h |
| Type: | 0 | | |
| Catagorius | LED | Calantamananatuna (IO) | 27001/ |

| Category: | LED | Color temperature (K): | 2700K |
|-----------|-----|------------------------|-----------------|
| Number: | 1 | Color Tolerance: | MacAdam 2SDCM |
| Watt: | 16W | Service Life: | L70 (6K) 50000h |
| Туре: | 0 | | |
| Category: | LED | Color temperature (K): | 2700K |
| Number: | 1 | Color Tolerance: | MacAdam 2SDCM |
| Watt: | 25W | Service Life: | L70 (6K) 50000h |
| Туре: | 0 | | |
| | | | |

LUMINAIRE

Watt: 25W + 16W Delivered lumens output (lm): 3126lm CCT: 2700K CRI:

Notes

*Uses 2 DALI addresses. Each module, angle and curved elements are provided with mechanical and electrical joints and installation accessories. 1 suspension cable in also included. End caps have to be ordered separately. Sharping kit (louvres and covers) has to be ordered separately.

PRODUCT DATA SHEET

ACCESSORIES



Suspension Accessories -Recessed Power Supply Kit For Suspension Modules (230VAC-48VDC 240W DALI) - White AQ15401



150W Bare power supply + plug 230VAC-48VDC IP20 -Undimmable (for dimmable version to be combined with "DALI-Selv interface") AQ18100



240W Bare power supply + plug 230VAC-48VDC IP20 -Undimmable (for dimmable version to be combined with "DALI-Selv interface") AQ18000



A.24 - Suspension Accessories -Ceiling Power Supply Kit For Suspension Modules (230VAC-48VDC 240W DALI) - White AQ16101



A.24 - Remote Box Power Supply Kit -313x243x57,5h -(230VAC-48VDC 240W DALI) AQ16000



A.24 - Suspension Accessories - End Cap (2x) - Brushed Bronze AQ45120



150W Ceiling power supply - kit 321x91x111H -230VAC-48VDC IP20 - Dimmable



Suspension Accessories -Recessed Power Supply Kit For Suspension Modules (230VAC-48VDC 240W DALI) - Black AQ15404



A.24 - Suspension Accessories -Ceiling Power Supply Kit For Suspension Modules (230VAC-48VDC 240W DALI) - Black AQ16104



240W Ceiling power supply kit -351x61x111H -230VAC-48VDC IP20 -Undimmable -Black AQ17104



150W Ceiling power supply kit -351x61x111H 230VAC-48VDC IP20 -Undimmable -Black AQ17604



A.24 - Insulating Spacer (1x) -Brushed Bronze DALI to DALI-Selv

Interface

103x67x21H AQ18200

150W Ceiling

321x91x111H -

230VAC-48VDC

IP20 - Dimmable

power supply - kit

150W Ceiling

351x61x111H -

230VAC-48VDC

Undimmable -

IP20 -

White

AQ17601

power supply kit -



A.24 - Suspension Accessories -Transition Cap -Brushed bronze AQ49420



A.24 - Sharping Kit L=1176mm -White AQ26001



240W Reccessed power supply kit -396x195x112H -230VAC-48VDC IP20 -Undimmable -White AQ17401



A.24 - Sharping Kit L=1176mm - Black AQ26004



240W Reccessed power supply kit -396x195x112H -230VAC-48VDC IP20 -Undimmable -Black AQ17404



240W Ceiling power supply kit -351x61x111H -230VAC-48VDC IP20 -Undimmable -White AQ17101