

# **A.39 Recessed Sharping Emission - Structural Module Trim - 1184mm - 20° - 3000K - Undimmable/Dimmable DALI - 2x4 Optics - Silver**



IP 20  Dimmerable: +  -

## **DESIGN BY**

Carlotta de Bevilacqua

## **DESCRIPTION**

## **TECHNICAL DRAWINGS**



## **FEATURES**

<b>Article Code:</b>	BH20005	<b>Series:</b>	Indoor
<b>Colour:</b>	Silver	<b>Emission:</b>	Direct
<b>Installation:</b>	Recessed		

## **DIMENSIONS**

<b>Length:</b>	cm 118
<b>Width:</b>	cm 5.5
<b>Recessed depth:</b>	cm 5.7

## **INCLUDED SOURCES**

<b>Category:</b>	LED	<b>Color temperature (K):</b>	3000K
<b>Number:</b>	1	<b>Color Tolerance:</b>	MacAdam 2SDCM
<b>Watt:</b>	22W	<b>Service Life:</b>	L90 (20K) 118000h
<b>Type:</b>	0		

## **LUMINAIRE**

<b>Watt:</b>	22W	<b>Delivered lumens output (lm):</b>	1648lm
		<b>CCT:</b>	3000K
		<b>Efficiency:</b>	76%
		<b>Efficacy:</b>	74.93lm/W
		<b>CRI:</b>	90
		<b>Dimmable Typology:</b>	Dali

## **Notes**

Driver 900mA SELV and screen supplied separately. Depending on the driver, the luminaire can be dimmable DALI or undimmable. \*Driver uses 1 DALI address

**ACCESSORIES**


Louvre - 1184mm  
2x4 optics white  
AE40001




Louvre - 1184mm  
2x4 optics black  
AE40004



A.39 Recessed -  
Trim End Cap (Kit  
2x) - Up to 15m -  
Silver  
AT09105




A.39 Recessed -  
Trim End Cap (Kit  
2x) - Up to 35m -  
Silver  
AT09205



Driver 60W -  
900mA - 220-240V  
- Undimmable  
DV1024



Sharping wall  
grazer lens Kit  
(4pcs) - 26°x70°  
elliptical lenses kit.  
It has to be used  
on top of S 20°  
reflectors to get  
an elliptical beam  
(greter axis along  
the module  
lenght). It contains  
4 lenses.  
AF06000



Driver 25W -  
900mA - 220-240V  
- Undimmable  
DV1022



A.39 Recessed -  
Trim End Cap (Kit  
2x) - Up to 5m -  
Silver  
AT09005