

A.39 Recessed Sharping Emission - Structural Module Trim - 1184mm - 20° - 4000K - Undimmable/Dimmable DALI - 3x4 Optics - Silver



IP 20  Dimmerable: 

DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

TECHNICAL DRAWINGS



FEATURES

Article Code:	BH21105	Series:	Indoor
Colour:	Silver	Emission:	Direct
Installation:	Recessed		

DIMENSIONS

Length:	cm 118
Width:	cm 5.5
Recessed depth:	cm 5.7

INCLUDED SOURCES

Category:	LED	Color temperature (K):	4000K
Number:	1	Color Tolerance:	MacAdam 2SDCM
Watt:	33W	Service Life:	L90 (20K) 118000h
Type:	0		

LUMINAIRE

Watt:	33W	Delivered lumens output (lm):	2646lm
		CCT:	4000K
		Efficiency:	76%
		Efficacy:	80.19lm/W
		CRI:	90
		Dimmable Typology:	Dali

Notes

Driver 900mA SELV and screen supplied separately. Depending on the driver, the luminaire can be dimmable DALI or undimmable. *Driver uses 1 DALI address

ACCESSORIES



Louvre - 1184mm
3x4 optics white
AE41001



Louvre - 1184mm
3x4 optics black
AE41004



A.39 Recessed -
Trim End Cap (Kit
2x) - Up to 15m -
Silver
AT09105




Driver 45W -
900mA - 220-240V
- Undimmable
DV1023



A.39 Recessed -
Trim End Cap (Kit
2x) - Up to 35m -
Silver
AT09205



Sharping wall
grazer lens Kit
(4pcs) - 26°x70°
elliptical lenses kit.
It has to be used
on top of S 20°
reflectors to get
an elliptical beam
(greter axis along
the module
lenght). It contains
4 lenses.
AF06000



Driver 45W -
900mA - 220-240V
- Undimmable
DV1025



A.39 Recessed -
Trim End Cap (Kit
2x) - Up to 5m -
Silver
AT09005