


A.39 Recessed Sharping Emission - Structural Module Trim - 1184mm - 36° - 4000K - Undimmable/Dimmable DALI - 2x4 Optics - Silver




IP 20  Dimmerable: +  -

DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

TECHNICAL DRAWINGS



FEATURES

Article Code:	BH20305	Series:	Indoor
Colour:	Silver	Emission:	Direct
Installation:	Recessed		

DIMENSIONS

Length:	cm 118
Width:	cm 5.5
Recessed depth:	cm 5.7

INCLUDED SOURCES

Category:	LED	Color temperature (K):	4000K
Number:	1	Color Tolerance:	MacAdam 2SDCM
Watt:	22W	Service Life:	L90 (20K) 118000h
Type:	0		

LUMINAIRE

Watt:	22W	Delivered lumens output (lm):	1651lm
		CCT:	4000K
		Efficiency:	71%
		Efficacy:	75.03lm/W
		CRI:	90
		Dimmable Typology:	Dali

Notes

Driver 900mA SELV and screen supplied separately. Depending on the driver, the luminaire can be dimmable DALI or undimmable. *Driver uses 1 DALI address

ACCESSORIES



Louvre - 1184mm
2x4 optics white
AE40001




Louvre - 1184mm
2x4 optics black
AE40004




A.39 Recessed -
Trim End Cap (Kit
2x) - Up to 15m -
Silver
AT09105



A.39 Recessed -
Trim End Cap (Kit
2x) - Up to 35m -
Silver
AT09205



Driver 60W -
900mA - 220-240V
- Undimmable
DV1024



Driver 25W -
900mA - 220-240V
- Undimmable
DV1022



A.39 Recessed -
Trim End Cap (Kit
2x) - Up to 5m -
Silver
AT09005