

A.39 Recessed Sharping Emission - Structural Module Trim - 2368mm - 20° - 3000K - Undimmable/Dimmable DALI - 6x4 Optics - White



IP 20  Dimmerable: +  -

DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

TECHNICAL DRAWINGS



FEATURES

Article Code:	BH23001	Series:	Indoor
Colour:	White	Emission:	Direct
Installation:	Recessed		

DIMENSIONS

Length:	cm 237
Width:	cm 5.5
Recessed depth:	cm 5.7

INCLUDED SOURCES

Category:	LED	Color temperature (K):	3000K
Number:	1	Color Tolerance:	MacAdam 2SDCM
Watt:	66W	Service Life:	L90 (20K) 118000h
Type:	0		

LUMINAIRE

Watt:	66W	Delivered lumens output (lm):	4945lm
		CCT:	3000K
		Efficiency:	76%
		Efficacy:	74.93lm/W
		CRI:	90
		Dimmable Typology:	Dali

Notes

Driver 900mA SELV and screen supplied separately. Depending on the driver, the luminaire can be dimmable DALI or undimmable. * Drivers use 2 DALI addresses.

ACCESSORIES


Louvre - 2368mm
6x4 optics - white
AE43001




Louvre - 2368mm
6x4 optics black
AE43004

NO
IMAGE
AVAILABLE


Sharping wall
grazer lens Kit
(4pcs) - 26°x70°
elliptical lenses kit.
It has to be used
on top of S 20°
reflectors to get
an elliptical beam
(greter axis along
the module
length). It contains
4 lenses.
AF06000



A.39 Recessed -
Trim End Cap (Kit
2x) - Up to 5m -
White
AT09001



Driver 45W -
900mA - 220-240V
- DALI
DV1027



Driver 45W -
900mA - 220-240V
- DALI
DV1029



A.39 Recessed -
Trim End Cap (Kit
2x) - Up to 15m -
White
AT09101



A.39 Recessed -
Trim End Cap (Kit
2x) - Up to 35m -
White
AT09201