

## A.39 Suspension - 1482mm - Direct + Indirect Emission - 3000K - DALI - Black



IP20  Dimmerable: +  -


### DESIGN BY

Carlotta de Bevilacqua

### DESCRIPTION

Controlled emission LED optic System. UGR index control and 65° luminance (EN 12464). Patent-pending proprietary optic system made by a thin black square-meshed grid and by a system of square plano-convex lenses of appropriate beam angle. The internal part of the grid is white painted and has a high reflection coefficient, so that the light incident on the grid is retrieved within the A.39 body. A net 'cut off' at the required angle is obtained through this system. The convex profile of the lens is designed with images optic techniques, so that the emission is limited within the 65° required by standard EN 12464. UGR<19 Angle luminance equals to 65° and beyond: <3,000 cd/m<sup>2</sup>. The grid positioned over the lenses allows only the rays falling into the required output angular limits to be incident to the lenses. The rays beyond these limits are recovered and redirected inside the light box (if the ray is incident to the white surface) or cancelled (if the ray is incident to the black edge).

### TECHNICAL DRAWINGS



### FEATURES

Article Code:	AT22404	Series:	Indoor
Colour:	Black		
Installation:	Suspension, Ceiling		

### DIMENSIONS

Length:	cm 148
Width:	cm 4,5
Height:	cm 8,5

### INCLUDED SOURCES

Category:	LED	Color temperature (K):	3000K
Number:	1		
Watt:	42W		
Type:	0		
Class:	A		
Category:	LED	Color temperature (K):	3000K
Number:	1	CRI:	80
Watt:	31W		
Type:	0		

### LUMINAIRE

Watt:	73W	Delivered lumens output (lm):	6315lm
		CCT:	3000K
		Efficiency:	61%
		Efficacy:	86.51lm/W
		CRI:	80
		Dimmable Typology:	Dali

### Notes

Screen supplied separately. Screen quantity to order: 1x M186700.

ACCESSORIES



A.39 - Mechanical joint including 1 suspension cable  
AT09500



Screen controlled emission - 1480mm (5 pcs)  
AT09900



End cap kit (2x) - Black  
AT09804



A.39 - Dimmable Feeding kit including 2 suspension cables (5 poles) 2000m (H)  
AT10500