

## A.39 Suspension - 2368mm - Direct + Indirect Emission - 3000K - Undimmable - Silver



IP20 


### DESIGN BY

Carlotta de Bevilacqua

### DESCRIPTION

Controlled emission LED optic System. UGR index control and 65° luminance (EN 12464). Patent-pending proprietary optic system made by a thin black square-meshed grid and by a system of square plano-convex lenses of appropriate beam angle. The internal part of the grid is white painted and has a high reflection coefficient, so that the light incident on the grid is retrieved within the A.39 body. A net 'cut off' at the required angle is obtained through this system. The convex profile of the lens is designed with images optic techniques, so that the emission is limited within the 65° required by standard EN 12464. UGR<19 Angle luminance equals to 65° and beyond: <3,000 cd/m<sup>2</sup>. The grid positioned over the lenses allows only the rays falling into the required output angular limits to be incident to the lenses. The rays beyond these limits are recovered and redirected inside the light box (if the ray is incident to the white surface) or cancelled (if the ray is incident to the black edge).

### TECHNICAL DRAWINGS



### FEATURES

Article Code:	AT23505	Series:	Indoor
Colour:	Silver		
Installation:	Suspension, Ceiling		

### DIMENSIONS

Length:	cm 237
Width:	cm 4.5
Height:	cm 8.5

### INCLUDED SOURCES

Category:	LED	Color temperature (K):	3000K
Number:	1	CRI:	80
Watt:	50W		
Type:	0		
Category:	LED	Color temperature (K):	3000K
Number:	1		
Watt:	66W		
Type:	0		
Class:	A		

### LUMINAIRE

Watt:	116W	Delivered lumens output (lm):	9711lm
		CCT:	3000K
		Efficiency:	60%
		Efficacy:	83.71lm/W
		CRI:	80

### Notes

Screen supplied separately. Screen quantity to order: 2x AT09900.

## ACCESSORIES

NO  
IMAGE  
AVAILABLE

A.39 - Mechanical  
joint including 1  
suspension cable  
AT09500



Algoritmo System  
LED - Optics -  
Controlled  
Emission -  
1184mm  
M186700

NO  
IMAGE  
AVAILABLE

A.39 -  
Undimmable  
Feeding kit  
including 2  
suspension cables  
(3 poles) 2000mm  
(H)  
AT10400

NO  
IMAGE  
AVAILABLE

End cap kit (2x) -  
Silver  
AT09805