A.39 Suspension - Direct + Indirect Emission - 1184mm - 36° - 4000K -Undimmable - 3x4 Optics - Black

DESIGN BY Carlotta de Bevilacqua


DESCRIPTION



IP 20 🕘 🐔 🕻 🕻

Artemide PRODUCT DATA SHEET

TECHNICAL DRAWINGS



Article Code:BH08504Series:IndoorColour:BlackInstallation:Suspension, CeilingDIMENSIONSLength:cm 118Width:cm 4.5Height:cm 8.5INCLUDED SOURCESCategory:LEDCategory:LEDColor Tolerance:MacAdWatt:38WService Life:L90 (20Type:4Category:LEDColor temperature (K):4000KNumber:1Color temperature (K):4000KNumber:1Color temperature (K):4000KNumber:1Color Tolerance:MacAdWatt:26WService Life:L90 (20Type:0LUMINAIRE64WWatt:64WDelivered lumens output (Im): 5564Irr CCT:CCT:4000KEfficiency:78%			FEATURES
Length: cm 118 Width: cm 4.5 Height: cm 8.5 INCLUDED SOURCES Category: LED Color temperature (K): 4000K Number: 1 Color Tolerance: MacAd Watt: 38W Service Life: L90 (20 Type: 4 Category: LED Color temperature (K): 4000K Number: 1 Color Tolerance: MacAd Watt: 26W Service Life: L90 (20 Type: 0 LUMINAIRE Watt: 64W Delivered lumens output (Im): 5564Im CCT: 4000K Efficiency: 78%		Black	Article Code: Colour:
Width:cm 4.5Height:cm 8.5INCLUDED SOURCESCategory:LEDColor temperature (K):4000KNumber:1Color Tolerance:MacAdWatt:38WService Life:L90 (20Type:4Color temperature (K):4000KCategory:LEDColor temperature (K):4000KNumber:1Color Tolerance:MacAdWatt:26WService Life:L90 (20Type:0Service Life:L90 (20LUMINAIREEugenerationStandardWatt:64WDelivered lumens output (Im): 5564Im CCT:5564Im 4000K 278%			DIMENSIONS
Category:LEDColor temperature (K):400KNumber:1Color Tolerance:MacAdWatt:38WService Life:L90 (20Type:4Color temperature (K):4000KCategory:LEDColor temperature (K):4000KNumber:1Color Tolerance:MacAdWatt:26WService Life:L90 (20Type:020LUMINAIRE64WDelivered lumens output (Im): 5564Im CCT:5564Im 4000K Efficiency:Watt:64WDelivered lumens output (Im): 5564Im CCT:78%		cm 4.5	Width:
Number:1Color Tolerance:MacAd.Watt:38WService Life:L90 (20Type:4Color temperature (K):4000KCategory:LEDColor temperature (K):4000KNumber:1Color Tolerance:MacAd.Watt:26WService Life:L90 (20Type:0Service Life:L90 (20LUMINAIREWatt:64WDelivered lumens output (Im): 5564Im CCT:CCT:4000KEfficiency:78%			INCLUDED SOURCES
Watt: 64W Delivered lumens output (Im): 5564Im CCT: 4000K Efficiency: 78%	Color Tolerance:MacAdam 2SDCMService Life:L90 (20K) 118000hColor temperature (K):4000KColor Tolerance:MacAdam 2SDCM	1 38W 4 LED 1 26W	Number: Watt: Type: Category: Number: Watt: Type:
CRI: 90	Efficiency: 78% Efficacy: 86.94lm/W	64W	Watt:

Notes

Screen supplied separately. *Driver uses 1 DALI addres



PRODUCT CODE: BH08504

ACCESSORIES



Louvre - 1184mm 3x4 optics white AE41001



Angle louvre - 90° corner screen (on same plane) -White BH44001



A.39 -Undimmable Feeding kit including 2 suspension cables (3 poles) 2000mm (H) AT10400

Louvre - 1184m	nm
3v4 ontics black	2

3x4 optics black AE41004



Angle louvre - 90° corner screen (on same plane) -Black BH44004



A.39 -Suspension/Ceiling - End Caps (2pcs) -Black BH16404

	NO	
	IMAGE	
Δ١		ļ

A.39 - Mechanical joint including 1 suspension cable AT09500

		NO)		
	1.0		_		
	IN	1A	Gl	-	
Δ	VA	II.	ΔF	15	F

A.39 -Suspension/Ceiling - Corner (on same plane) - Black BH35004