

A.39 Suspension - Direct + Indirect Emission - 1184mm - 52° - 3000K -Undimmable - 2x4 Optics - Silver

DESIGN BY Carlotta de Bevilacqua


DESCRIPTION



IP 20 🔔

Artemide PRODUCT DATA SHEET

TECHNICAL DRAWINGS



FEATURES			
FEATURES			
Article Code:	BH12805	Series:	Indoor
Colour:	Silver		
Installation:	Suspension, Ceiling		
DIMENSIONS			
Length:	cm 118		
Width:	cm 4.5		
Height:	cm 8.5		
INCLUDED SOURCES			
Category:	LED	Color temperature (K):	3000K
Number:	1	Color Tolerance:	MacAdam 2SDCM
Watt:	25W	Service Life:	L90 (20K) 118000h
Туре:	0		
Category:	LED	Color temperature (K):	3000K
Number:	1	Color Tolerance:	MacAdam 2SDCM
Watt:	26W	Service Life:	L90 (20K) 118000h
Туре:	0		
LUMINAIRE			
Watt:	53W	Delivered lumens output (l	m): 4553lm
		CCT:	3000K
		Efficiency:	81%
		Efficacy:	85.91lm/W
		CRI:	90
Notes			

Screen supplied separately. *Driver uses 1 DALI addres



PRODUCT CODE: BH12805

ACCESSORIES



2x4 optics white AE40001



Angle louvre - 90° corner screen (on same plane) -White BH44001



A.39 -Suspension/Ceiling - Corner (on same plane) - Silver BH35005

Louvre - 1184m	nm
2v4 ontics black	





Angle louvre - 90° corner screen (on same plane) -Black BH44004



Suspension/Ceiling - End Caps (2pcs) -Silver BH16405

NO		
IMAGE		
AVAILAB	L	Į

A.39 - Mechanical joint including 1 suspension cable AT09500

1.0		_	_	
	MA	G	-	
Δ17	AIL	ΛΓ	15	5

A.39 -Undimmable Feeding kit including 2 suspension cables (3 poles) 2000mm (H) AT10400