

March 2019


# A.39 Suspension - Direct + Indirect Emission - 2368mm - 36° - 4000K -Undimmable - 4x4 Optics - Silver



IP 20 🔔

Artemide PRODUCT DATA SHEET

### TECHNICAL DRAWINGS



FEATURES			
Article Code: Colour: Installation:	BH14505 Silver Suspension, Ceiling	Series:	Indoor
DIMENSIONS			
Length: Width: Height:	cm 237 cm 4.5 cm 8.5		
INCLUDED SOURCES			
Category: Number: Watt: Type: Category: Number: Watt: Type: LUMINAIRE	LED 1 50W 0 LED 1 54W 0	Color temperature (K): Color Tolerance: Service Life: Color temperature (K): Color Tolerance: Service Life:	4000K MacAdam 2SDCM L90 (20K) 118000h 4000K MacAdam 2SDCM L90 (20K) 118000h
Watt:	104W	Delivered lumens output (l CCT: Efficiency: Efficacy: CRI:	l <b>m):</b> 9478lm 4000K 80% 91.14lm/W 90
Notes			

Screen supplied separately. \*Driver uses 1 DALI addres

We reserve the right to change our product specifications. Please visit www.artemide.com for the latest product information

## DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION



## PRODUCT CODE: BH14505

#### ACCESSORIES



4x4 optics white AE42001



Angle louvre - 90° corner screen (on same plane) -White BH44001

NO	
IMAGE	
AVAILABLE	

A.39 -Suspension/Ceiling - Corner (on same plane) - Silver BH35005

Louvre - 2368m	m
Aut a stigg la la al	

4x4 optics black AE42004



Angle louvre - 90° corner screen (on same plane) -Black BH44004

	NO
	IMAGE
	AVAILABLE
L	
A	<b>\</b> .39 -

Suspension/Ceiling - End Caps (2pcs) -Silver BH16405

	NO	
	IMAGE	
Δ١	/ΔII ΔRI	Į

A.39 - Mechanical joint including 1 suspension cable AT09500

1.0		_	_	
	MA	G	-	
Δ17	AIL	ΛΓ	15	5

A.39 -Undimmable Feeding kit including 2 suspension cables (3 poles) 2000mm (H) AT10400