


A.39 Suspension - Structural Module 1482mm - Direct + Indirect Emission - 4000K - DALI - White



IP20  Dimmerable: 


DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

Optimized version in line applications with wide lengths. Diffusing direct and direct + indirect emission. Recessed trim, trimless, suspension and ceiling versions. Dimmable and non dimmable in two CCT 3000K and 4000K versions.

TECHNICAL DRAWINGS



FEATURES

Article Code:	AT22201	Series:	Indoor
Colour:	White		
Installation:	Ceiling		
Environment:	Indoor		

DIMENSIONS

Length:	cm 148
Width:	cm 4.5
Height:	cm 8.5

INCLUDED SOURCES

Category:	LED	Color temperature (K):	4000K
Number:	1		
Watt:	42W		
Type:	0		
Class:	A		
Category:	LED	Color temperature (K):	4000K
Number:	1		
Watt:	31W		
Type:	0		
Class:	A		

LUMINAIRE

Watt:	42W + 31W	Delivered lumens output (lm):	2704lm + 4118lm
		CCT:	4000K
		CRI:	80
		Dimmable Typology:	Dali

ACCESSORIES



A.39 - Mechanical joint including 1 suspension cable
AT09500



A.39 - End Cap (Kit 2x) - White
AT09401



A.39 - Opal Diffuser in Polycarbonate - L=10000mm
AT10000



A.39 - Dimmable Feeding kit including 2 suspension cables (5 poles) 2000m (H)
AT10500



A.39 - Opal Diffuser in Polycarbonate - L=25000mm
AT10800



A.39 - Opal Diffuser in Polycarbonate - L=50000mm
AT10900