



## A.39 Suspension - Structural Module 2960mm - Direct + Indirect Emission - 3000K - Undimmable - Silver



IP20 


### DESIGN BY

Carlotta de Bevilacqua

### DESCRIPTION

Optimized version in line applications with wide lengths. Diffusing direct and direct + indirect emission. Recessed trim, trimless, suspension and ceiling versions. Dimmable and non dimmable in two CCT 3000K and 4000K versions.

### TECHNICAL DRAWINGS



### FEATURES

Article Code:	AT24105	Series:	Indoor
Colour:	Silver		
Installation:	Ceiling		
Environment:	Indoor		

### DIMENSIONS

Length:	cm 296
Width:	cm 4.5
Height:	cm 8.5

### INCLUDED SOURCES

Category:	LED	Color temperature (K):	3000K
Number:	1		
Watt:	82W		
Type:	0		
Class:	A		
Category:	LED	Color temperature (K):	3000K
Number:	1		
Watt:	67W		
Type:	0		
Class:	A		

### LUMINAIRE

Watt:	82W + 67W	Delivered lumens output (lm):	4732lm + 7883lm
		CCT:	3000K
		CRI:	80

ACCESSORIES



A.39 - Mechanical joint including 1 suspension cable AT09500



A.39 - Opal Diffuser in Polycarbonate - L=10000mm AT10000



A.39 - Undimmable Feeding kit including 2 suspension cables (3 poles) 2000mm (H) AT10400



A.39 - Opal Diffuser in Polycarbonate - L=25000mm AT10800



A.39 - Opal Diffuser in Polycarbonate - L=50000mm AT10900



A.39 - End Cap (Kit 2x) - Silver AT09405



A.39 - Opal Diffuser in Polycarbonate - L=2960mm AT10300