
PRODUCT DATA SHEET PRODUCT CODE: AT14301

A.39 Suspension/Ceiling - Structural Module 1482mm - Direct Emission - 4000K - Undimmable - White



IP20 **⊕**


DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

Optimized version in line applications with wide lenghts. Diffusing direct and direct + indirect emission. Recessed trim, trimless, suspension and ceiling versions. Dimmable and non dimmable in two CCT 3000K and 4000K versions.

TECHNICAL DRAWINGS



FEATURES

Width:

Height:

Article Code: Colour: Installation: Environment:	AT14301 White Ceiling Indoor	Series:	Indoor
DIMENSIONS			
Length:	cm 148		

Color temperature (K):

4000K

INCLUDED SOURCES

 Category:
 LED

 Number:
 1

 Watt:
 42W

 Type:
 0

 Class:
 A

LUMINAIRE

 Watt:
 42W
 Delivered lumens output (Im): 2704lm

 CCT:
 4000K

 CRI:
 80

cm 4 5

cm 8.5



ACCESSORIES

NO IMAGE AVAILABLE

A.39 - Mechanical joint including 1 suspension cable AT09500

NO IMAGE AVAILABLE

A.39 - End Ceiling Bracket (2x) AT09502 IMAGE AVAILABLE

NO

A.39 - End Cap (Kit 2x) - White AT09401

> NO IMAGE AVAILABLE

A.39 - Opal Diffuser in Polycarbonate -L=10000mm AT10000 NO IMAGE AVAILABLE

A.39 - Ceiling bracket and mechanical joint AT09501

> NO IMAGE AVAILABLE

A.39 -Undimmable Feeding kit including 2 suspension cables (3 poles) 2000mm (H) AT10400

NO IMAGE AVAILABLE

A.39 - Opal Diffuser in Polycarbonate -L=25000mm AT10800 NO IMAGE AVAILABLE

A.39 - Opal Diffuser in Polycarbonate -L=50000mm AT10900