

A. Sharping Wired Gear Plates Sharping LED Direct Emission - 1184mm 25W 36° 3000K



IP20  Dimmerable: 


DESIGN BY

Carlotta de Bevilacqua

DESCRIPTION

Algoritmo Sharping is very flexible and it allows to combine in continuity Sharp light modules, with indirect and diffused LED lighting in warm white (3000K) and neutral white (4000K). Structural modules are in extruded aluminum, available in different lengths depending on the installation option, three finishes (white, black, silver or gloss anodized), two optic finishes (black and white) and three beams (20°, 36° and 52°).

TECHNICAL DRAWINGS



FEATURES

Article Code:	AE00100	Series:	Indoor
Colour:	White		
Installation:	Recessed, Wall, Suspension, Ceiling		
Environment:	Indoor		

DIMENSIONS

Length:	cm 118
----------------	--------

INCLUDED SOURCES

Category:	LED	Color temperature (K):	3000K
Number:	1	Color Tolerance:	MacAdam 2SDCM
Watt:	25W	Service Life:	L90 (20K) 118000h
Type:	0		
Class:	A		

LUMINAIRE

Watt:	25W	Delivered lumens output (lm):	1542lm
		CCT:	3000K
		Efficiency:	71%
		Efficacy:	61.70lm/W
		CRI:	90
		Dimmable Typology:	Dali

Notes

MV integrated through-cable. Protection screen for indirect LED wired plate included.