

Algoritmo System for Projectors - 37 Cube - 3x8W 14° 4000K



IP20 💮

DESIGN BY

Carlotta de Bevilacqua, Paola di Arianello

DESCRIPTION

PAD is a projectors using high-efficiency led with monochromatic warm white (3000K) and neutral white (4000K) emission. Comprised of an aluminium body with bright anodized finish and a translucent cover in polycarbonate. Pad is available in four mounting options: with three-phase track adapter, with base plate or recessed plate for ceiling mounting, and in combination with the Algoritmo product line. The array of 12 leds (13W in total) lays on a metal core placed on the aluminium body of the projector that acts as heat dissipator. The special power supply system is housed within the body, thus allowing a direct connection to the electrical network (100-240V). The cover acts as a support for the lenses available in 3 beam options. It provides a diffused lighting effect while ensuring protection for the electrical parts. A smart hinge that combines reduced dimensions with a very large angular excursion provides extreme flexibility of rotation: rotation of up to 358°, tilt angle of up to +90°/-90°. Complies with EN60598-1 and other specific standards. An extension of the PAD family, PAD SQUARE houses an array of 24 LEDs (26W in total) placed on the aluminium body that acts as heat dissipator. The special, patented electrical system houses the power supply within the shell, and allows a direct connection to the electrical network. A translucent cover in polycarbonate closes off the body. It acts as a support for the various lenses, ensures protection for the electrical parts and provides a diffused lighting effect. Rotation of up to 358°, tilt angle of up to 180°. 4 installation options: with adaptor for 3-circuit track, with gear plate for mounting within Algoritmo product range, wall/ceiling mounted version, or base plate for semi- recessed mounting. Complies with EN60598-1 and other specific standards. 37 Cube is a Led spotlight with extremely small dimensions (37x37x37mm) featuring a perfect balance between size and luminous flux: the device is visually out of the way, whilst all the attention is aimed at the lighting effects in the room. The body in extruded aluminium is completed by a translucent shell that receives the interchangeable lenses (2x7° / 2x9° / 2x14°) and provides a diffused lighting effect. The minimalistic volumes breathe light into a new quality, from both the architectural and technical lighting standpoint as well as in terms of sustainability and savings. Adjustable by 358° along the vertical axis and by 90° along the horizontal axis, they provide accurate and effective accent lighting with only 7 Watts of used power. The extremely compact size of 37 Cube allows it to be installed together with the Algoritmo product line, as it can be completely housed inside the modules. Materials: body in extruded aluminium, screen / lens holder in satin-finish polycarbonate. Complies with EN62471, EN60598 and other specific standards.

ECHI	NICAL DR	AWING	15	
40				
Ē				
77 80				
	98,5 197 591	37		

FEATURES			
Article Code:	M029400	Material:	Aluminium and
Colour:	Bright polished		polycarbonate
	aluminium	Series:	Indoor
Installation:	Projector, Recessed, Ceiling	Area contract:	Hospitality, null, null, Retail, Culture, Residential
		Emission:	Accent lighting
DIMENSIONS			
Width:	cm 4	Glow Wire Test:	650
Height:	cm 7.7		
Weight:	kg 0.5		
Inclination:	cm 90		
Rotation:	cm 360		
INCLUDED SOURCES			
Category:	LED	Color Rendering:	>80
Number:	3	Color temperature (K):	4000K
Watt:	7W	Color Tolerance:	4SDCM
Delivered lumens output (lm)	: 565lm	CRI:	=80 (typ)
Type:	0	Efficacy:	81lm/W
Class:	А	Service Life:	L70(6K) > 50000h
LUMINAIRE			
Trasformer availability:	Included in the	Delivered lumens output (lm)	: 517lm
	Algoritmo pre-wired		4000K
	gearplate to be	Efficiency:	100%
	ordered separately	Efficacy:	64.62lm/W
Watt:	8.0W	CRI:	80
Voltage:	230-240V		March 2019
on			

We reserve the right to change our product specifications. Please visit www.artemide.com for the latest product information



ACCESSORIES

NO IMAGE AVAILABLE
Algoritmo System
intermediate
finishing
connector (set of 2
pcs). To be used at
the junction of
modules with
accent lighting and
fluorescent or LED
modules. Metal-
grey paint finish.
M217660

	N	С
	IMA	GE
A	VAIL	ABLE

Algoritmo System blind panel 591mm long. To be placed for the empty positions (i.e. where no accent lighting unit is used). Metalgrey. M217560