
Aria Micro - 2,5W 3000K - IP40 - Black



IP40 🕥

TECHNICAL DRAWINGS



DESCRIPTION

Light fixture with high-performance LED light sources. Wall or ceiling installation. Composed by: frame, body, asymmetrical reflector, fixing springs or housing. Body in injection mould of aluminium. Frame in aluminium. Body and frame are painted with outdoor treatment three stages: nanotechnologies, antioxidant primer, polyester paint. Metalized polycarbonate reflector. Silicone gasket. Protection screen in tempered glass, 3mm-thick. Housing in bend metal. Electrical connection to the ballast by means of a cable with appropriate terminal board supplied with the fixture. White monochromatic LEDs available in 2 colour temperatures: Warm = 3000K Neutral = 4000K IP Rating IP65 or IP40. Insulation class III. Technical features of light fixtures in compliance with EN60598-1. Installation must be carried out by specialized personnel. Carefully follow the instructions.

FEATURES			
Article Code: Colour: Installation:	NL31018VTK004 Black Wall, Ceiling	Material:	Aluminum, polycarbonate, tempered glass
Environment:	Outdoor	Series:	Outdoor
DIMENSIONS			
Length:	cm 6	Cutout shape:	Squared
Height:	cm 6		
Weight:	kg 0.6		
Recessed depth:	cm 3		
INCLUDED SOURCES	5		
Category:	LED	Color temperature (K):	3000K
Number:	1	Color Tolerance:	MacAdam 4SDCM)
Watt:	2,5W	CRI:	=80(min.)
Delivered lumens output (lm): 165lm		Efficacy:	72lm/W
Туре:	0	Service Life:	L70(10K)>60500h
Class:	А		
LUMINAIRE			
Watt:	2,5W	Delivered lumens output (lm): 57lm	
		сст:	3000K
		Efficiency:	100%
		Efficacy:	21.11lm/W
		CRI:	80



ACCESSORIES

Cassaforma Aria Micro NL31020H0

NO IMAGE AVAILABLE		
Alimentatore 5	,6W	
350mA IP67		
DV3001		
	-	
]	
NO		
NO IMAGE		

NO IMAGE AVAILABLE
Alimentatore 11.2W 700mA

11,2W 700r IP67 DV3003

NO	
IMAGE	
AVAILABLE	

Alimentatore 35W 350mA IP67 DV3004

