

# Aria Mini - 6W 3000K - IP40 - Black




IP40 🕼

### **DESCRIPTION**

Light fixture with high-performance LED light sources. Wall or ceiling installation. Composed by: frame, body, asymmetrical reflector, fixing springs or housing. Body in injection mould of aluminium. Frame in aluminium. Body and frame are painted with outdoor treatment three stages: nanotechnologies, antioxidant primer, polyester paint. Metalized polycarbonate reflector. Silicone gasket. Protection screen in tempered glass, 3mm-thick. Housing in bend metal. Electrical connection to the ballast by means of a cable with appropriate terminal board supplied with the fixture. White monochromatic LEDs available in 2 colour temperatures: Warm = 3000K Neutral = 4000K IP Rating IP65 or IP40. Insulation class III. Technical features of light fixtures in compliance with EN60598-1. Installation must be carried out by specialized personnel. Carefully follow the instructions.

## **TECHNICAL DRAWINGS**



### **FEATURES**

Article Code: Colour: Installation: Environment:	AJ30004 Black Wall, Ceiling Outdoor	Material: Series:	Aluminum, polycarbonate, tempered glass Outdoor
DIMENSIONS			
Length:	cm 10	Cutout shape:	Squared
Height:	cm 10	·	,
Weight:	kg 0.6		
Recessed depth:	cm 4.8		
INCLUDED SOURCES			
Category:	LED	Color temperature (K):	3000K
Number:	1	•	
Watt:	6W		
Type:	0		
Class:	Α		

6W

 Delivered lumens output (Im):
 204lm

 CCT:
 3000K

 Efficiency:
 35%

 Efficacy:
 34.00lm/W

 CRI:
 85



# ACCESSORIES

NO IMAGE AVAILABLE

ALIMENT. 8,4W 350mA (indip.) NL19032

> NO IMAGE AVAILABLE

ALIMENT. 20W 700mA (indip.) NL19036

NO IMAGE AVAILABLE

Area Mini Cassaforma AJ90000 NO IMAGE AVAILABLE

ALIMENT. 12W 700mA IP67 NL19024

> NO IMAGE AVAILABLE

ALIMENT. 35W 700mA IP67 NL19029 NO IMAGE AVAILABLE

ALIMENT. 5W 350mA IP67 NL11022

> NO IMAGE AVAILABLE

ALIMENT. 9,8W 700mA (indip.) NL19035