PRODUCT DATA SHEET PRODUCT CODE: 1052010A

Castore suspension 35



DESIGN BY


Michele De Lucchi, Huub Ubbens

DESCRIPTION

The spherical diffuser design is enhanced by a removable-fitting and tapering luminous stem, that makes a sweet transition from the strong diffuser light to the blind lamp structure area. Ceiling rose and stem in thermoplastic resin, blown glass diffuser.

TECHNICAL DRAWINGS

Dimmerable: + 10-



FEATURES

| Article Code: Colour: | 1052010A White | Material: | Blown glass, polycarbonate |
|--------------------------|-------------------|----------------|-------------------------------|
| Installation: | Suspension | Series: | Design |
| Environment: | Indoor | Area contract: | Hospitality, Retail, |
| | | | Residential |
| | | Emission: | Diffused |

DIMENSIONS

| Height: | cm 83 | Glow Wire Test: | 750 |
|--------------------------|--------|-----------------|-----|
| Base Diameter: | cm 15 | | |
| Max Height from ceiling: | cm 233 | | |

NOT INCLUDED SOURCES

| Category: | HALO | Color Rendering: | 1a |
|-----------|------|------------------------|-------|
| Number: | 1 | Color temperature (K): | 2900K |
| Watt: | 150W | | |
| Lbs: | Qt32 | | |

E27

2000h

ALTERNATIVE SOURCES

| Category: | LED | |
|-------------------------------------|-----|--|
| Number: | 1 | |
| Watt: | 21W | |
| Delivered lumens output (lm):2452lm | | |
| Туре: | 2 | |
| Socket: | E27 | |
| Class: | Α | |

LUMINAIRE

Socket: Duration (h):

| Watt: | 150W | Delivered lumens output (lm):2431lm | |
|----------|-----------|-------------------------------------|--------|
| Voltage: | 220V-240V | CCT: | 3000K |
| | | Efficiency: | 85% |
| | | Efficacy: | 16lm/W |

CRI: 99

Notes

Available in four sizes.