
PRODUCT DATA SHEET PRODUCT CODE: T42121LW00

Effetto Round 1 large beam Gray/white



IP65 □ **⑤ ⑤**


DESIGN BY

Ernesto Gismondi

DESCRIPTION

Light fixture with 1 light beam using monochromatic LED light source caracterized by warm colour temperature (3000K) together with a light-diffusing lens which optimize the optical performance of the beam and establish its width. Designed to create geometric lights of scenic effect, it has 1 narrow beam of 15°. Wall installation. Composed by lighting cap unit and terminal board fixed together by means of locking dowels. Cap in die-cast EN AB-47100 aluminium. Terminal board in reinforced polymer. Watertight gasket in silicone rubber. Locking dowels used outside the fixture in AISI 316 stainless steel. PMMA lens siliconed flush with the cap to obtain the beam angle opening.

TECHNICAL DRAWINGS



FEATURES

FEATURES			
Article Code: Colour: Installation: Environment:	T42121LW00 Gray/white Wall Outdoor	Material:	Aluminum, composite technopolymer, methacrylate
		Series: Area contract:	Outdoor Urban, Outdoor, Residential
		Emission:	Indirect
DIMENSIONS			
Width:	cm 14	Impact Resistance:	IK10

INCLUDED SOURCES

Category:	LED	Color temperature (K):	3000K
Number:	1	Color Tolerance:	4SDCM
Watt:	4,5W	CRI:	80 typ
Delivered lumens output (lm):178lm		Efficacy:	85lm/W
Туре:	0	Service Life:	L70(14K)>81600
Class:	Α		

Glow Wire Test:

650

LUMINAIRE

Power Supply:	Electronic Integr	Electronic Integrated Delivered lumens output (lm):54,5lm		
Watt:	4,5W	CCT:	3000K	
Voltage:	220V-240V	Efficiency:	100%	
		Efficacy:	10.85lm/W	
		CRI:	80	

Notes

Wiring to be carried out inside the terminal board by piercing an IP65 membrane grommet suitable for cables with a diameter of 6-13 mm. Painted die-cast aluminium with 3-stage outdoor treatment: nanotechnologies, antioxidant primer, polyester paint. Effective power 2,7W.



