

# Ego 150 downlight Round 5° 3000K



IP 65/67 (1)


#### **DESIGN BY**

Studio Artemide

#### **DESCRIPTION**

Light fixture with high-performance LED light sources. Ceiling installation. Two different housing depths. Round and square version in five sizes. Consists of body, frame, black silkscreened tempered glass, fixing springs. Body in EN AB44100 aluminium, silicone gaskets. Frame in aluminium or stainless steel AISI 316. Black silkscreened tempered glass, 8mm-thick. Fixing springs in harmonic iron. Power connection to the mains by means of a H05RN-r cabl and IP68 electrical terminal board, supplied with the fixture. Glass surface temperature lower than 40°C. Fixed or adjustable optics. PMMA lenses in 3 different versions of beams. White monochromatic LEDs available in 2 colour temperatures Warm = 3000K Neutral = 4000K Painted diecast aluminium with 3-stage outdoortreatment: nanotechnologies, anti-oxidant primer, polyester paint. Technical features of light fixtures in compliance with EN60598-1 and part 2-13. IP Rating IP65. Insulation class III. Installation must be carried out by specialized personnel. Carefully follow the instructions.

#### **TECHNICAL DRAWINGS**



## **FEATURES**

Article Code: Installation:	T4130NSPW00 Recessed	Series:	Outdoor
DIMENSIONS			
Recessed depth:	cm 12.6	Cutout diameter: Cutout shape: Impact Resistance:	cm 13.5 Rounded IK10
INCLUDED SOURCES			
Category: Number: Watt: Wattage (Single): Delivered lumens output (Im) Type: Class: LUMINAIRE	LED 1 8W 2W : 382Im 0 A	Color temperature (K): Color Tolerance: CRI: Efficacy: Service Life:	3000K MacAdam 4SDCM 80 64lm/W L70(10K) > 60500h
Watt:	8W	Delivered lumens output (lm) CCT: Efficiency: Efficacy:	: 366lm 3000K 100% 45.75lm/W

CRI:

### Notes

Flood opticWide luminous flow suitable for lighting large areas.

80



## ACCESSORIES

NO IMAGE AVAILABLE

CASSAFORMA ORCAMO DL 150R T409919