

Granito 60 Rust



IP65    


DESIGN BY

Ernesto Gismondi

DESCRIPTION

Outdoor lamp. The four light beams projected through the fissures on the sides make it particularly suitable for lighting drives or to create light effects in parks and gardens. Cor-ten (weathering steel) structure, which is distinguished for its high resistance to corrosion and high mechanical resistance.

TECHNICAL DRAWINGS



FEATURES

Article Code:	T083100	Material:	Cor-ten steel, glass
Colour:	Rust	Series:	Outdoor
Installation:	Bollard, Floor	Area contract:	null
Environment:	Outdoor	Emission:	Direct

DIMENSIONS

Width:	cm 30	Impact Resistance:	IK10
Height:	cm 60		

NOT INCLUDED SOURCES

Category:	HQI	Color Rendering:	80
Number:	1	Color temperature (K):	3000K
Watt:	35W		
Lbs:	HIT-CE		
Socket:	G12		

LUMINAIRE

Power Supply:	Electronic
Watt:	35W
Voltage:	220V-240V

Notes

Notices The product is manufactured using corten steel plate. Corten steel is coated with a natural oxide layer that becomes 'stable' 16/24 months from installation. Before stabilisation, corten steel may release rust powder that may stain the surfaces where it is placed. Artemide recommends not to position it on sensitive surfaces such as light-coloured stone, marble, etc. Appearance The colour of corten steel may change in time depending on weather conditions and exposure to sunlight. The colour becomes stable after 16/24 and takes on a 'tobacco' hue. Care The product received a treatment that reduces, but does not eliminate, release of rust powder. If necessary, this treatment should be repeated by the customer until oxide stabilisation. Apply wood-care bee's wax using a soft cloth.